



PROJECT REPORT

For the

**U.S. Corp of Engineers High Resolution LiDAR Data Acquisition & Processing for
portions of Connecticut**

**USACE Contract:
W912P9-10-D-0534**

**Task Order Number:
0002**

**Prepared for:
USDANRCS**

Prepared by:
Dewberry
1000 Ashley Blvd., Suite 801
Tampa, Florida 33602-3718

Report Date: September 8, 2011

Table of Contents

Executive Summary	3
1 Project Tiling Footprint	5
1.1 List of delivered tiles (4,840):.....	6
2 LiDAR Acquisition Report	35
2.1 PROJECT DESCRIPTION.....	35
2.2 MISSION PLANNING.....	35
2.3 ACQUISITION.....	37
2.4 PROCESSING	39
2.5 QA/QC.....	40
2.6 Final Deliverables	42
3 LiDAR Processing & Qualitative Assessment.....	42
3.1 Data Classification and Editing	42
3.2 Qualitative Assessment.....	44
3.4 Conclusion	50
3 Survey Vertical Accuracy Checkpoints	50
4.1 Survey Checkpoints not used in vertical accuracy testing	52
5 LiDAR Vertical Accuracy Statistics & Analysis	54
5.1 Background.....	54
5.2 Vertical Accuracy Test Procedures.....	54
5.3 Vertical Accuracy Testing Steps.....	55
5.4 Vertical Accuracy Results	56
5.5 Conclusion	59
6 Breakline Production & Qualitative Assessment Report.....	59
6.1 Breakline Production Methodology	59
6.2 Breakline Qualitative Assessment	60
6.3 Breakline Topology Rules	60
6.4 Breakline QA/QC Checklist	61
6.5 Data Dictionary.....	63
6.5.1 Horizontal and Vertical Datum	64
6.5.2 Coordinate System and Projection	64
6.5.3 Inland Streams and Rivers.....	64
6.5.4 Inland Ponds and Lakes.....	65
7 DEM Production & Qualitative Assessment.....	67

7.1	DEM Production Methodology	67
7.2	DEM Qualitative Assessment	68
7.3	DEM QA/QC Checklist	69

Executive Summary

The primary purpose of this project was to develop a consistent and accurate surface elevation dataset derived from high-accuracy Light Detection and Ranging (LiDAR) technology for use by USDA-NRCS Connecticut in such projects as conservation planning, floodplain mapping, dam safety assessments, and hydrologic modeling.

The LiDAR data were processed to a bare-earth digital elevation model (DEM). Detailed breaklines, bare-earth DEMs, and multiple LiDAR derivatives were produced for the project area. Data was formatted according to tiles with each tile covering an area of 1000 m by 1000 m. A total of 4,840 tiles were produced for the project encompassing an area of approximately 4,589 sq. kilometers.

The Project Team

Dewberry served as the prime contractor for the project. In addition to project management, Dewberry was responsible for LAS classification, all LiDAR products, breakline production, Digital Elevation Model (DEM) production, and quality assurance.

Dewberry's IES offices completed ground surveying for the project and delivered surveyed checkpoints. Their task was to acquire surveyed checkpoints for the project to use in independent testing of the vertical accuracy of the LiDAR-derived surface model. They also verified the GPS base station coordinates used during LiDAR data acquisition to ensure that the base station coordinates were accurate. Note that a separate Survey Report was created for this portion of the project.

Earth Eye completed LiDAR data acquisition and data calibration for the project area.

Survey Area

The project area addressed by this report covers all of the Connecticut counties of Tolland and Windham and portions of the Connecticut counties of Hartford, Middlesex, and New London.

Date of Survey

The LiDAR aerial acquisition was conducted from November 3, 2010 thru December 11, 2010.

Datum Reference

Data produced for the project were delivered in the following reference system.

Horizontal Datum: The horizontal datum for the project is North American Datum of 1983 (NAD 83)

Vertical Datum: The Vertical datum for the project is North American Vertical Datum of 1988 (NAVD88)

Coordinate System: UTM Zone 18N

Units: Horizontal units are in meters, Vertical units are in meters.

Geoid Model: Geoid09 (Geoid 09 was used to convert ellipsoid heights to orthometric heights).

LiDAR Vertical Accuracy

For the Connecticut LiDAR Project, the tested $RMSE_z$ for open terrain checkpoints equaled **0.05 m** compared with the 0.0925 m specification; and the FVA computed using $RMSE_z \times 1.9600$ was equal to **0.09 m**, compared with the 0.185 m specification.

For the Connecticut LiDAR Project, the tested CVA computed using the 95th percentile was equal to **0.17 m**, compared with the 0.185 m specification.

Project Deliverables

The deliverables for the project are listed below.

1. Classified Point Cloud LiDAR Data (Tiled)
2. Bare Earth LiDAR Data (Tiled)
3. First Return LiDAR Data (Tiled)
4. Last Return LiDAR Data (Tiled)
5. Model Key Point LiDAR Data (Tiled)
6. Bare Earth Surface (Raster DEM – GRID Format)
7. Control & Accuracy Checkpoint Report & Points
8. Metadata
9. Project Report (Acquisition, Processing, QC)
10. Project Extents
11. Breakline Data (File GDB)
12. Intensity Imagery (GeoTIFF Format with 0.3 m pixels)

1 Project Tiling Footprint

Four thousand eight hundred and forty (4,840) tiles were delivered for the project. Each tile's extent is 1000 meters by 1000 meters.




Figure 1: Project Map

1.1 List of delivered tiles (4,840):

18TXM9525	18TXM9831	18TXM9927	18TXM0014
18TXM9526	18TXM9832	18TYM9928	18TXM0015
18TXM9527	18TXM9833	18TXM9929	18TXM0016
18TXM9624	18TXM9834	18TYM9930	18TXM0017
18TXM9625	18TXM9837	18TXM9931	18TYM0018
18TXM9626	18TXM9840	18TXM9932	18TYM0019
18TXM9627	18TXM9841	18TXM9933	18TYM0020
18TXM9628	18TXM9842	18TXM9934	18TYM0021
18TXM9629	18TXM9843	18TXM9935	18TYM0022
18TXM9704	18TXM9844	18TXM9936	18TYM0023
18TXM9705	18TXM9845	18TXM9937	18TYM0024
18TXM9706	18TXM9846	18TXM9938	18TYM0025
18TXM9707	18TXM9847	18TXM9939	18TYM0026
18TXM9723	18TXM9848	18TYM9940	18TYM0027
18TXM9724	18TXM9851	18TYM9941	18TYM0028
18TXM9725	18TXM9852	18TXM9942	18TYM0029
18TXM9726	18TXM9853	18TXM9943	18TYM0030
18TXM9727	18TXM9854	18TXM9944	18TYM0031
18TXM9728	18TXM9904	18TXM9945	18TYM0032
18TXM9729	18TXM9905	18TXM9946	18TYM0033
18TXM9730	18TXM9906	18TXM9947	18TYM0034
18TXM9731	18TXM9907	18TXM9948	18TYM0035
18TXM9804	18TXM9908	18TXM9949	18TYM0036
18TXM9805	18TXM9909	18TXM9950	18TYM0037
18TXM9806	18TXM9910	18TXM9951	18TYM0038
18TXM9807	18TXM9911	18TXM9952	18TYM0039
18TXM9811	18TXM9912	18TXM9953	18TYM0040
18TXM9812	18TXM9913	18TXM9954	18TYM0041
18TXM9813	18TXM9914	18TXM9955	18TYM0042
18TXM9814	18TXM9915	18TXM0003	18TYM0043
18TXM9815	18TXM9916	18TXM0004	18TYM0044
18TXM9822	18TXM9917	18TXM0005	18TYM0045
18TXM9823	18TXM9918	18TXM0006	18TXM0046
18TXM9824	18TYM9919	18TXM0007	18TXM0047
18TXM9825	18TXM9921	18TXM0008	18TXM0048
18TXM9826	18TYM9922	18TXM0009	18TXM0049
18TXM9827	18TXM9923	18TXM0010	18TXM0050
18TXM9828	18TXM9924	18TXM0011	18TXM0051
18TXM9829	18TXM9925	18TXM0012	18TXM0052
18TXM9830	18TXM9926	18TXM0013	18TXM0053

18TXM0054	18TYM0143	18TYM0232	18TYM0321
18TXM0055	18TYM0144	18TYM0233	18TYM0322
18TYM0056	18TYM0145	18TYM0234	18TYM0323
18TYM0103	18TYM0146	18TYM0235	18TYM0324
18TYM0104	18TYM0147	18TYM0236	18TYM0325
18TYM0105	18TYM0148	18TYM0237	18TYM0326
18TYM0106	18TYM0149	18TYM0238	18TYM0327
18TYM0107	18TYM0150	18TYM0239	18TYM0328
18TYM0108	18TYM0151	18TYM0240	18TYM0329
18TYM0109	18TYM0152	18TYM0241	18TYM0330
18TYM0110	18TYM0153	18TYM0242	18TYM0331
18TYM0111	18TYM0154	18TYM0243	18TYM0332
18TYM0112	18TYM0155	18TYM0244	18TYM0333
18TYM0113	18TYM0156	18TYM0245	18TYM0334
18TYM0114	18TYM0203	18TYM0246	18TYM0335
18TYM0115	18TYM0204	18TYM0247	18TYM0336
18TYM0116	18TYM0205	18TYM0248	18TYM0337
18TYM0117	18TYM0206	18TYM0249	18TYM0338
18TYM0118	18TYM0207	18TYM0250	18TYM0339
18TYM0119	18TYM0208	18TYM0251	18TYM0340
18TYM0120	18TYM0209	18TYM0252	18TYM0341
18TYM0121	18TYM0210	18TYM0253	18TYM0342
18TYM0122	18TYM0211	18TYM0254	18TYM0343
18TYM0123	18TYM0212	18TYM0255	18TYM0344
18TYM0124	18TYM0213	18TYM0256	18TYM0345
18TYM0125	18TYM0214	18TYM0303	18TYM0346
18TYM0126	18TYM0215	18TYM0304	18TYM0347
18TYM0127	18TYM0216	18TYM0305	18TYM0348
18TYM0128	18TYM0217	18TYM0306	18TYM0349
18TYM0129	18TYM0218	18TYM0307	18TYM0350
18TYM0130	18TYM0219	18TYM0308	18TYM0351
18TYM0131	18TYM0220	18TYM0309	18TYM0352
18TYM0132	18TYM0221	18TYM0310	18TYM0353
18TYM0133	18TYM0222	18TYM0311	18TYM0354
18TYM0134	18TYM0223	18TYM0312	18TYM0355
18TYM0135	18TYM0224	18TYM0313	18TYM0356
18TYM0136	18TYM0225	18TYM0314	18TYL0498
18TYM0137	18TYM0226	18TYM0315	18TYL0499
18TYM0138	18TYM0227	18TYM0316	18TYL0400
18TYM0139	18TYM0228	18TYM0317	18TYM0401
18TYM0140	18TYM0229	18TYM0318	18TYM0402
18TYM0141	18TYM0230	18TYM0319	18TYM0403
18TYM0142	18TYM0231	18TYM0320	18TYM0404

18TYM0405	18TYM0448	18TYM0531	18TYM0614
18TYM0406	18TYM0449	18TYM0532	18TYM0615
18TYM0407	18TYM0450	18TYM0533	18TYM0616
18TYM0408	18TYM0451	18TYM0534	18TYM0617
18TYM0409	18TYM0452	18TYM0535	18TYM0618
18TYM0410	18TYM0453	18TYM0536	18TYM0619
18TYM0411	18TYM0454	18TYM0537	18TYM0620
18TYM0412	18TYM0455	18TYM0538	18TYM0621
18TYM0413	18TYM0456	18TYM0539	18TYM0622
18TYM0414	18TYL0597	18TYM0540	18TYM0623
18TYM0415	18TYL0598	18TYM0541	18TYM0624
18TYM0416	18TYL0599	18TYM0542	18TYM0625
18TYM0417	18TYL0500	18TYM0543	18TYM0626
18TYM0418	18TYM0501	18TYM0544	18TYM0627
18TYM0419	18TYM0502	18TYM0545	18TYM0628
18TYM0420	18TYM0503	18TYM0546	18TYM0629
18TYM0421	18TYM0504	18TYM0547	18TYM0630
18TYM0422	18TYM0505	18TYM0548	18TYM0631
18TYM0423	18TYM0506	18TYM0549	18TYM0632
18TYM0424	18TYM0507	18TYM0550	18TYM0633
18TYM0425	18TYM0508	18TYM0551	18TYM0634
18TYM0426	18TYM0509	18TYM0552	18TYM0635
18TYM0427	18TYM0510	18TYM0553	18TYM0636
18TYM0428	18TYM0511	18TYM0554	18TYM0637
18TYM0429	18TYM0512	18TYM0555	18TYM0638
18TYM0430	18TYM0513	18TYM0556	18TYM0639
18TYM0431	18TYM0514	18TYL0697	18TYM0640
18TYM0432	18TYM0515	18TYL0698	18TYM0641
18TYM0433	18TYM0516	18TYL0699	18TYM0642
18TYM0434	18TYM0517	18TYL0600	18TYM0643
18TYM0435	18TYM0518	18TYM0601	18TYM0644
18TYM0436	18TYM0519	18TYM0602	18TYM0645
18TYM0437	18TYM0520	18TYM0603	18TYM0646
18TYM0438	18TYM0521	18TYM0604	18TYM0647
18TYM0439	18TYM0522	18TYM0605	18TYM0648
18TYM0440	18TYM0523	18TYM0606	18TYM0649
18TYM0441	18TYM0524	18TYM0607	18TYM0650
18TYM0442	18TYM0525	18TYM0608	18TYM0651
18TYM0443	18TYM0526	18TYM0609	18TYM0652
18TYM0444	18TYM0527	18TYM0610	18TYM0653
18TYM0445	18TYM0528	18TYM0611	18TYM0654
18TYM0446	18TYM0529	18TYM0612	18TYM0655
18TYM0447	18TYM0530	18TYM0613	18TYM0656

18TYL0796	18TYM0739	18TYM0820	18TYM0901
18TYL0797	18TYM0740	18TYM0821	18TYM0902
18TYL0798	18TYM0741	18TYM0822	18TYM0903
18TYL0799	18TYM0742	18TYM0823	18TYM0904
18TYL0700	18TYM0743	18TYM0824	18TYM0905
18TYM0701	18TYM0744	18TYM0825	18TYM0906
18TYM0702	18TYM0745	18TYM0826	18TYM0907
18TYM0703	18TYM0746	18TYM0827	18TYM0908
18TYM0704	18TYM0747	18TYM0828	18TYM0909
18TYM0705	18TYM0748	18TYM0829	18TYM0910
18TYM0706	18TYM0749	18TYM0830	18TYM0911
18TYM0707	18TYM0750	18TYM0831	18TYM0912
18TYM0708	18TYM0751	18TYM0832	18TYM0913
18TYM0709	18TYM0752	18TYM0833	18TYM0914
18TYM0710	18TYM0753	18TYM0834	18TYM0915
18TYM0711	18TYM0754	18TYM0835	18TYM0916
18TYM0712	18TYM0755	18TYM0836	18TYM0917
18TYM0713	18TYM0756	18TYM0837	18TYM0918
18TYM0714	18TYL0895	18TYM0838	18TYM0919
18TYM0715	18TYL0896	18TYM0839	18TYM0920
18TYM0716	18TYL0897	18TYM0840	18TYM0921
18TYM0717	18TYL0898	18TYM0841	18TYM0922
18TYM0718	18TYL0899	18TYM0842	18TYM0923
18TYM0719	18TYL0800	18TYM0843	18TYM0924
18TYM0720	18TYM0801	18TYM0844	18TYM0925
18TYM0721	18TYM0802	18TYM0845	18TYM0926
18TYM0722	18TYM0803	18TYM0846	18TYM0927
18TYM0723	18TYM0804	18TYM0847	18TYM0928
18TYM0724	18TYM0805	18TYM0848	18TYM0929
18TYM0725	18TYM0806	18TYM0849	18TYM0930
18TYM0726	18TYM0807	18TYM0850	18TYM0931
18TYM0727	18TYM0808	18TYM0851	18TYM0932
18TYM0728	18TYM0809	18TYM0852	18TYM0933
18TYM0729	18TYM0810	18TYM0853	18TYM0934
18TYM0730	18TYM0811	18TYM0854	18TYM0935
18TYM0731	18TYM0812	18TYM0855	18TYM0936
18TYM0732	18TYM0813	18TYM0856	18TYM0937
18TYM0733	18TYM0814	18TYL0995	18TYM0938
18TYM0734	18TYM0815	18TYL0996	18TYM0939
18TYM0735	18TYM0816	18TYL0997	18TYM0940
18TYM0736	18TYM0817	18TYL0998	18TYM0941
18TYM0737	18TYM0818	18TYL0999	18TYM0942
18TYM0738	18TYM0819	18TYL0900	18TYM0943

18TYM0944	18TYM1025	18TYM1103	18TYM1146
18TYM0945	18TYM1026	18TYM1104	18TYM1147
18TYM0946	18TYM1027	18TYM1105	18TYM1148
18TYM0947	18TYM1028	18TYM1106	18TYM1149
18TYM0948	18TYM1029	18TYM1107	18TYM1150
18TYM0949	18TYM1030	18TYM1108	18TYM1151
18TYM0950	18TYM1031	18TYM1109	18TYM1152
18TYM0951	18TYM1032	18TYM1110	18TYM1153
18TYM0952	18TYM1033	18TYM1111	18TYM1154
18TYM0953	18TYM1034	18TYM1112	18TYM1155
18TYM0954	18TYM1035	18TYM1113	18TYM1156
18TYM0955	18TYM1036	18TYM1114	18TYL1291
18TYM0956	18TYM1037	18TYM1115	18TYL1292
18TYL1095	18TYM1038	18TYM1116	18TYL1293
18TYL1096	18TYM1039	18TYM1117	18TYL1294
18TYL1097	18TYM1040	18TYM1118	18TYL1295
18TYL1098	18TYM1041	18TYM1119	18TYL1296
18TYL1099	18TYM1042	18TYM1120	18TYL1297
18TYL1000	18TYM1043	18TYM1121	18TYL1298
18TYM1001	18TYM1044	18TYM1122	18TYL1299
18TYM1002	18TYM1045	18TYM1123	18TYL1200
18TYM1003	18TYM1046	18TYM1124	18TYM1201
18TYM1004	18TYM1047	18TYM1125	18TYM1202
18TYM1005	18TYM1048	18TYM1126	18TYM1203
18TYM1006	18TYM1049	18TYM1127	18TYM1204
18TYM1007	18TYM1050	18TYM1128	18TYM1205
18TYM1008	18TYM1051	18TYM1129	18TYM1206
18TYM1009	18TYM1052	18TYM1130	18TYM1207
18TYM1010	18TYM1053	18TYM1131	18TYM1208
18TYM1011	18TYM1054	18TYM1132	18TYM1209
18TYM1012	18TYM1055	18TYM1133	18TYM1210
18TYM1013	18TYM1056	18TYM1134	18TYM1211
18TYM1014	18TYL1192	18TYM1135	18TYM1212
18TYM1015	18TYL1193	18TYM1136	18TYM1213
18TYM1016	18TYL1194	18TYM1137	18TYM1214
18TYM1017	18TYL1195	18TYM1138	18TYM1215
18TYM1018	18TYL1196	18TYM1139	18TYM1216
18TYM1019	18TYL1197	18TYM1140	18TYM1217
18TYM1020	18TYL1198	18TYM1141	18TYM1218
18TYM1021	18TYL1199	18TYM1142	18TYM1219
18TYM1022	18TYL1100	18TYM1143	18TYM1220
18TYM1023	18TYM1101	18TYM1144	18TYM1221
18TYM1024	18TYM1102	18TYM1145	18TYM1222

18TYM1223	18TYL1399	18TYM1342	18TYM1416
18TYM1224	18TYL1300	18TYM1343	18TYM1417
18TYM1225	18TYM1301	18TYM1344	18TYM1418
18TYM1226	18TYM1302	18TYM1345	18TYM1419
18TYM1227	18TYM1303	18TYM1346	18TYM1420
18TYM1228	18TYM1304	18TYM1347	18TYM1421
18TYM1229	18TYM1305	18TYM1348	18TYM1422
18TYM1230	18TYM1306	18TYM1349	18TYM1423
18TYM1231	18TYM1307	18TYM1350	18TYM1424
18TYM1232	18TYM1308	18TYM1351	18TYM1425
18TYM1233	18TYM1309	18TYM1352	18TYM1426
18TYM1234	18TYM1310	18TYM1353	18TYM1427
18TYM1235	18TYM1311	18TYM1354	18TYM1428
18TYM1236	18TYM1312	18TYM1355	18TYM1429
18TYM1237	18TYM1313	18TYM1356	18TYM1430
18TYM1238	18TYM1314	18TYL1488	18TYM1431
18TYM1239	18TYM1315	18TYL1489	18TYM1432
18TYM1240	18TYM1316	18TYL1490	18TYM1433
18TYM1241	18TYM1317	18TYL1491	18TYM1434
18TYM1242	18TYM1318	18TYL1492	18TYM1435
18TYM1243	18TYM1319	18TYL1493	18TYM1436
18TYM1244	18TYM1320	18TYL1494	18TYM1437
18TYM1245	18TYM1321	18TYL1495	18TYM1438
18TYM1246	18TYM1322	18TYL1496	18TYM1439
18TYM1247	18TYM1323	18TYL1497	18TYM1440
18TYM1248	18TYM1324	18TYL1498	18TYM1441
18TYM1249	18TYM1325	18TYL1499	18TYM1442
18TYM1250	18TYM1326	18TYL1400	18TYM1443
18TYM1251	18TYM1327	18TYM1401	18TYM1444
18TYM1252	18TYM1328	18TYM1402	18TYM1445
18TYM1253	18TYM1329	18TYM1403	18TYM1446
18TYM1254	18TYM1330	18TYM1404	18TYM1447
18TYM1255	18TYM1331	18TYM1405	18TYM1448
18TYM1256	18TYM1332	18TYM1406	18TYM1449
18TYL1390	18TYM1333	18TYM1407	18TYM1450
18TYL1391	18TYM1334	18TYM1408	18TYM1451
18TYL1392	18TYM1335	18TYM1409	18TYM1452
18TYL1393	18TYM1336	18TYM1410	18TYM1453
18TYL1394	18TYM1337	18TYM1411	18TYM1454
18TYL1395	18TYM1338	18TYM1412	18TYM1455
18TYL1396	18TYM1339	18TYM1413	18TYM1456
18TYL1397	18TYM1340	18TYM1414	18TYL1588
18TYL1398	18TYM1341	18TYM1415	18TYL1589

18TYL1590	18TYM1533	18TYM1605	18TYM1648
18TYL1591	18TYM1534	18TYM1606	18TYM1649
18TYL1592	18TYM1535	18TYM1607	18TYM1650
18TYL1593	18TYM1536	18TYM1608	18TYM1651
18TYL1594	18TYM1537	18TYM1609	18TYM1652
18TYL1595	18TYM1538	18TYM1610	18TYM1653
18TYL1596	18TYM1539	18TYM1611	18TYM1654
18TYL1597	18TYM1540	18TYM1612	18TYM1655
18TYL1598	18TYM1541	18TYM1613	18TYM1656
18TYL1599	18TYM1542	18TYM1614	18TYL1785
18TYL1500	18TYM1543	18TYM1615	18TYL1786
18TYM1501	18TYM1544	18TYM1616	18TYL1787
18TYM1502	18TYM1545	18TYM1617	18TYL1788
18TYM1503	18TYM1546	18TYM1618	18TYL1789
18TYM1504	18TYM1547	18TYM1619	18TYL1790
18TYM1505	18TYM1548	18TYM1620	18TYL1791
18TYM1506	18TYM1549	18TYM1621	18TYL1792
18TYM1507	18TYM1550	18TYM1622	18TYL1793
18TYM1508	18TYM1551	18TYM1623	18TYL1794
18TYM1509	18TYM1552	18TYM1624	18TYL1795
18TYM1510	18TYM1553	18TYM1625	18TYL1796
18TYM1511	18TYM1554	18TYM1626	18TYL1797
18TYM1512	18TYM1555	18TYM1627	18TYL1798
18TYM1513	18TYM1556	18TYM1628	18TYL1799
18TYM1514	18TYL1686	18TYM1629	18TYL1700
18TYM1515	18TYL1687	18TYM1630	18TYM1701
18TYM1516	18TYL1688	18TYM1631	18TYM1702
18TYM1517	18TYL1689	18TYM1632	18TYM1703
18TYM1518	18TYL1690	18TYM1633	18TYM1704
18TYM1519	18TYL1691	18TYM1634	18TYM1705
18TYM1520	18TYL1692	18TYM1635	18TYM1706
18TYM1521	18TYL1693	18TYM1636	18TYM1707
18TYM1522	18TYL1694	18TYM1637	18TYM1708
18TYM1523	18TYL1695	18TYM1638	18TYM1709
18TYM1524	18TYL1696	18TYM1639	18TYM1710
18TYM1525	18TYL1697	18TYM1640	18TYM1711
18TYM1526	18TYL1698	18TYM1641	18TYM1712
18TYM1527	18TYL1699	18TYM1642	18TYM1713
18TYM1528	18TYL1600	18TYM1643	18TYM1714
18TYM1529	18TYM1601	18TYM1644	18TYM1715
18TYM1530	18TYM1602	18TYM1645	18TYM1716
18TYM1531	18TYM1603	18TYM1646	18TYM1717
18TYM1532	18TYM1604	18TYM1647	18TYM1718

18TYM1719	18TYL1890	18TYM1833	18TYM1903
18TYM1720	18TYL1891	18TYM1834	18TYM1904
18TYM1721	18TYL1892	18TYM1835	18TYM1905
18TYM1722	18TYL1893	18TYM1836	18TYM1906
18TYM1723	18TYL1894	18TYM1837	18TYM1907
18TYM1724	18TYL1895	18TYM1838	18TYM1908
18TYM1725	18TYL1896	18TYM1839	18TYM1909
18TYM1726	18TYL1897	18TYM1840	18TYM1910
18TYM1727	18TYL1898	18TYM1841	18TYM1911
18TYM1728	18TYL1899	18TYM1842	18TYM1912
18TYM1729	18TYL1800	18TYM1843	18TYM1913
18TYM1730	18TYM1801	18TYM1844	18TYM1914
18TYM1731	18TYM1802	18TYM1845	18TYM1915
18TYM1732	18TYM1803	18TYM1846	18TYM1916
18TYM1733	18TYM1804	18TYM1847	18TYM1917
18TYM1734	18TYM1805	18TYM1848	18TYM1918
18TYM1735	18TYM1806	18TYM1849	18TYM1919
18TYM1736	18TYM1807	18TYM1850	18TYM1920
18TYM1737	18TYM1808	18TYM1851	18TYM1921
18TYM1738	18TYM1809	18TYM1852	18TYM1922
18TYM1739	18TYM1810	18TYM1853	18TYM1923
18TYM1740	18TYM1811	18TYM1854	18TYM1924
18TYM1741	18TYM1812	18TYM1855	18TYM1925
18TYM1742	18TYM1813	18TYM1856	18TYM1926
18TYM1743	18TYM1814	18TYL1984	18TYM1927
18TYM1744	18TYM1815	18TYL1985	18TYM1928
18TYM1745	18TYM1816	18TYL1986	18TYM1929
18TYM1746	18TYM1817	18TYL1987	18TYM1930
18TYM1747	18TYM1818	18TYL1988	18TYM1931
18TYM1748	18TYM1819	18TYL1989	18TYM1932
18TYM1749	18TYM1820	18TYL1990	18TYM1933
18TYM1750	18TYM1821	18TYL1991	18TYM1934
18TYM1751	18TYM1822	18TYL1992	18TYM1935
18TYM1752	18TYM1823	18TYL1993	18TYM1936
18TYM1753	18TYM1824	18TYL1994	18TYM1937
18TYM1754	18TYM1825	18TYL1995	18TYM1938
18TYM1755	18TYM1826	18TYL1996	18TYM1939
18TYM1756	18TYM1827	18TYL1997	18TYM1940
18TYL1885	18TYM1828	18TYL1998	18TYM1941
18TYL1886	18TYM1829	18TYL1999	18TYM1942
18TYL1887	18TYM1830	18TYL1900	18TYM1943
18TYL1888	18TYM1831	18TYM1901	18TYM1944
18TYL1889	18TYM1832	18TYM1902	18TYM1945

18TYM1946	18TYM2016	18TYL2182	18TYM2125
18TYM1947	18TYM2017	18TYL2183	18TYM2126
18TYM1948	18TYM2018	18TYL2184	18TYM2127
18TYM1949	18TYM2019	18TYL2185	18TYM2128
18TYM1950	18TYM2020	18TYL2186	18TYM2129
18TYM1951	18TYM2021	18TYL2187	18TYM2130
18TYM1952	18TYM2022	18TYL2188	18TYM2131
18TYM1953	18TYM2023	18TYL2189	18TYM2132
18TYM1954	18TYM2024	18TYL2190	18TYM2133
18TYM1955	18TYM2025	18TYL2191	18TYM2134
18TYM1956	18TYM2026	18TYL2192	18TYM2135
18TYL2084	18TYM2027	18TYL2193	18TYM2136
18TYL2085	18TYM2028	18TYL2194	18TYM2137
18TYL2086	18TYM2029	18TYL2195	18TYM2138
18TYL2087	18TYM2030	18TYL2196	18TYM2139
18TYL2088	18TYM2031	18TYL2197	18TYM2140
18TYL2089	18TYM2032	18TYL2198	18TYM2141
18TYL2090	18TYM2033	18TYL2199	18TYM2142
18TYL2091	18TYM2034	18TYL2100	18TYM2143
18TYL2092	18TYM2035	18TYM2101	18TYM2144
18TYL2093	18TYM2036	18TYM2102	18TYM2145
18TYL2094	18TYM2037	18TYM2103	18TYM2146
18TYL2095	18TYM2038	18TYM2104	18TYM2147
18TYL2096	18TYM2039	18TYM2105	18TYM2148
18TYL2097	18TYM2040	18TYM2106	18TYM2149
18TYL2098	18TYM2041	18TYM2107	18TYM2150
18TYL2099	18TYM2042	18TYM2108	18TYM2151
18TYL2000	18TYM2043	18TYM2109	18TYM2152
18TYM2001	18TYM2044	18TYM2110	18TYM2153
18TYM2002	18TYM2045	18TYM2111	18TYM2154
18TYM2003	18TYM2046	18TYM2112	18TYM2155
18TYM2004	18TYM2047	18TYM2113	18TYM2156
18TYM2005	18TYM2048	18TYM2114	18TYL2280
18TYM2006	18TYM2049	18TYM2115	18TYL2281
18TYM2007	18TYM2050	18TYM2116	18TYL2282
18TYM2008	18TYM2051	18TYM2117	18TYL2283
18TYM2009	18TYM2052	18TYM2118	18TYL2284
18TYM2010	18TYM2053	18TYM2119	18TYL2285
18TYM2011	18TYM2054	18TYM2120	18TYL2286
18TYM2012	18TYM2055	18TYM2121	18TYL2287
18TYM2013	18TYM2056	18TYM2122	18TYL2288
18TYM2014	18TYL2180	18TYM2123	18TYL2289
18TYM2015	18TYL2181	18TYM2124	18TYL2290

18TYL2291	18TYM2234	18TYL2300	18TYM2343
18TYL2292	18TYM2235	18TYM2301	18TYM2344
18TYL2293	18TYM2236	18TYM2302	18TYM2345
18TYL2294	18TYM2237	18TYM2303	18TYM2346
18TYL2295	18TYM2238	18TYM2304	18TYM2347
18TYL2296	18TYM2239	18TYM2305	18TYM2348
18TYL2297	18TYM2240	18TYM2306	18TYM2349
18TYL2298	18TYM2241	18TYM2307	18TYM2350
18TYL2299	18TYM2242	18TYM2308	18TYM2351
18TYL2200	18TYM2243	18TYM2309	18TYM2352
18TYM2201	18TYM2244	18TYM2310	18TYM2353
18TYM2202	18TYM2245	18TYM2311	18TYM2354
18TYM2203	18TYM2246	18TYM2312	18TYM2355
18TYM2204	18TYM2247	18TYM2313	18TYM2356
18TYM2205	18TYM2248	18TYM2314	18TYL2480
18TYM2206	18TYM2249	18TYM2315	18TYL2481
18TYM2207	18TYM2250	18TYM2316	18TYL2482
18TYM2208	18TYM2251	18TYM2317	18TYL2483
18TYM2209	18TYM2252	18TYM2318	18TYL2484
18TYM2210	18TYM2253	18TYM2319	18TYL2485
18TYM2211	18TYM2254	18TYM2320	18TYL2486
18TYM2212	18TYM2255	18TYM2321	18TYL2487
18TYM2213	18TYM2256	18TYM2322	18TYL2488
18TYM2214	18TYL2380	18TYM2323	18TYL2489
18TYM2215	18TYL2381	18TYM2324	18TYL2490
18TYM2216	18TYL2382	18TYM2325	18TYL2491
18TYM2217	18TYL2383	18TYM2326	18TYL2492
18TYM2218	18TYL2384	18TYM2327	18TYL2493
18TYM2219	18TYL2385	18TYM2328	18TYL2494
18TYM2220	18TYL2386	18TYM2329	18TYL2495
18TYM2221	18TYL2387	18TYM2330	18TYL2496
18TYM2222	18TYL2388	18TYM2331	18TYL2497
18TYM2223	18TYL2389	18TYM2332	18TYL2498
18TYM2224	18TYL2390	18TYM2333	18TYL2499
18TYM2225	18TYL2391	18TYM2334	18TYL2400
18TYM2226	18TYL2392	18TYM2335	18TYM2401
18TYM2227	18TYL2393	18TYM2336	18TYM2402
18TYM2228	18TYL2394	18TYM2337	18TYM2403
18TYM2229	18TYL2395	18TYM2338	18TYM2404
18TYM2230	18TYL2396	18TYM2339	18TYM2405
18TYM2231	18TYL2397	18TYM2340	18TYM2406
18TYM2232	18TYL2398	18TYM2341	18TYM2407
18TYM2233	18TYL2399	18TYM2342	18TYM2408

18TYM2409	18TYM2452	18TYM2517	18TYL2681
18TYM2410	18TYM2453	18TYM2518	18TYL2682
18TYM2411	18TYM2454	18TYM2519	18TYL2683
18TYM2412	18TYM2455	18TYM2520	18TYL2684
18TYM2413	18TYM2456	18TYM2521	18TYL2685
18TYM2414	18TYL2579	18TYM2522	18TYL2686
18TYM2415	18TYL2580	18TYM2523	18TYL2687
18TYM2416	18TYL2581	18TYM2524	18TYL2688
18TYM2417	18TYL2582	18TYM2525	18TYL2689
18TYM2418	18TYL2583	18TYM2526	18TYL2690
18TYM2419	18TYL2584	18TYM2527	18TYL2691
18TYM2420	18TYL2585	18TYM2528	18TYL2692
18TYM2421	18TYL2586	18TYM2529	18TYL2693
18TYM2422	18TYL2587	18TYM2530	18TYL2694
18TYM2423	18TYL2588	18TYM2531	18TYL2695
18TYM2424	18TYL2589	18TYM2532	18TYL2696
18TYM2425	18TYL2590	18TYM2533	18TYL2697
18TYM2426	18TYL2591	18TYM2534	18TYL2698
18TYM2427	18TYL2592	18TYM2535	18TYL2699
18TYM2428	18TYL2593	18TYM2536	18TYM2600
18TYM2429	18TYL2594	18TYM2537	18TYM2601
18TYM2430	18TYL2595	18TYM2538	18TYM2602
18TYM2431	18TYL2596	18TYM2539	18TYM2603
18TYM2432	18TYL2597	18TYM2540	18TYM2604
18TYM2433	18TYL2598	18TYM2541	18TYM2605
18TYM2434	18TYL2599	18TYM2542	18TYM2606
18TYM2435	18TYL2500	18TYM2543	18TYM2607
18TYM2436	18TYM2501	18TYM2544	18TYM2608
18TYM2437	18TYM2502	18TYM2545	18TYM2609
18TYM2438	18TYM2503	18TYM2546	18TYM2610
18TYM2439	18TYM2504	18TYM2547	18TYM2611
18TYM2440	18TYM2505	18TYM2548	18TYM2612
18TYM2441	18TYM2506	18TYM2549	18TYM2613
18TYM2442	18TYM2507	18TYM2550	18TYM2614
18TYM2443	18TYM2508	18TYM2551	18TYM2615
18TYM2444	18TYM2509	18TYM2552	18TYM2616
18TYM2445	18TYM2510	18TYM2553	18TYM2617
18TYM2446	18TYM2511	18TYM2554	18TYM2618
18TYM2447	18TYM2512	18TYM2555	18TYM2619
18TYM2448	18TYM2513	18TYM2556	18TYM2620
18TYM2449	18TYM2514	18TYL2678	18TYM2621
18TYM2450	18TYM2515	18TYL2679	18TYM2622
18TYM2451	18TYM2516	18TYL2680	18TYM2623

18TYM2624	18TYL2787	18TYM2730	18TYL2891
18TYM2625	18TYL2788	18TYM2731	18TYL2892
18TYM2626	18TYL2789	18TYM2732	18TYL2893
18TYM2627	18TYL2790	18TYM2733	18TYL2894
18TYM2628	18TYL2791	18TYM2734	18TYL2895
18TYM2629	18TYL2792	18TYM2735	18TYL2896
18TYM2630	18TYL2793	18TYM2736	18TYL2897
18TYM2631	18TYL2794	18TYM2737	18TYL2898
18TYM2632	18TYL2795	18TYM2738	18TYL2899
18TYM2633	18TYL2796	18TYM2739	18TYM2800
18TYM2634	18TYL2797	18TYM2740	18TYM2801
18TYM2635	18TYL2798	18TYM2741	18TYM2802
18TYM2636	18TYL2799	18TYM2742	18TYM2803
18TYM2637	18TYM2700	18TYM2743	18TYM2804
18TYM2638	18TYM2701	18TYM2744	18TYM2805
18TYM2639	18TYM2702	18TYM2745	18TYM2806
18TYM2640	18TYM2703	18TYM2746	18TYM2807
18TYM2641	18TYM2704	18TYM2747	18TYM2808
18TYM2642	18TYM2705	18TYM2748	18TYM2809
18TYM2643	18TYM2706	18TYM2749	18TYM2810
18TYM2644	18TYM2707	18TYM2750	18TYM2811
18TYM2645	18TYM2708	18TYM2751	18TYM2812
18TYM2646	18TYM2709	18TYM2752	18TYM2813
18TYM2647	18TYM2710	18TYM2753	18TYM2814
18TYM2648	18TYM2711	18TYM2754	18TYM2815
18TYM2649	18TYM2712	18TYM2755	18TYM2816
18TYM2650	18TYM2713	18TYM2756	18TYM2817
18TYM2651	18TYM2714	18TYL2875	18TYM2818
18TYM2652	18TYM2715	18TYL2876	18TYM2819
18TYM2653	18TYM2716	18TYL2877	18TYM2820
18TYM2654	18TYM2717	18TYL2878	18TYM2821
18TYM2655	18TYM2718	18TYL2879	18TYM2822
18TYM2656	18TYM2719	18TYL2880	18TYM2823
18TYL2777	18TYM2720	18TYL2881	18TYM2824
18TYL2778	18TYM2721	18TYL2882	18TYM2825
18TYL2779	18TYM2722	18TYL2883	18TYM2826
18TYL2780	18TYM2723	18TYL2884	18TYM2827
18TYL2781	18TYM2724	18TYL2885	18TYM2828
18TYL2782	18TYM2725	18TYL2886	18TYM2829
18TYL2783	18TYM2726	18TYL2887	18TYM2830
18TYL2784	18TYM2727	18TYL2888	18TYM2831
18TYL2785	18TYM2728	18TYL2889	18TYM2832
18TYL2786	18TYM2729	18TYL2890	18TYM2833

18TYM2834	18TYL2995	18TYM2938	18TYM3001
18TYM2835	18TYL2996	18TYM2939	18TYM3002
18TYM2836	18TYL2997	18TYM2940	18TYM3003
18TYM2837	18TYL2998	18TYM2941	18TYM3004
18TYM2838	18TYL2999	18TYM2942	18TYM3005
18TYM2839	18TYM2900	18TYM2943	18TYM3006
18TYM2840	18TYM2901	18TYM2944	18TYM3007
18TYM2841	18TYM2902	18TYM2945	18TYM3008
18TYM2842	18TYM2903	18TYM2946	18TYM3009
18TYM2843	18TYM2904	18TYM2947	18TYM3010
18TYM2844	18TYM2905	18TYM2948	18TYM3011
18TYM2845	18TYM2906	18TYM2949	18TYM3012
18TYM2846	18TYM2907	18TYM2950	18TYM3013
18TYM2847	18TYM2908	18TYM2951	18TYM3014
18TYM2848	18TYM2909	18TYM2952	18TYM3015
18TYM2849	18TYM2910	18TYM2953	18TYM3016
18TYM2850	18TYM2911	18TYM2954	18TYM3017
18TYM2851	18TYM2912	18TYM2955	18TYM3018
18TYM2852	18TYM2913	18TYM2956	18TYM3019
18TYM2853	18TYM2914	18TYL3077	18TYM3020
18TYM2854	18TYM2915	18TYL3078	18TYM3021
18TYM2855	18TYM2916	18TYL3079	18TYM3022
18TYM2856	18TYM2917	18TYL3080	18TYM3023
18TYL2975	18TYM2918	18TYL3081	18TYM3024
18TYL2976	18TYM2919	18TYL3082	18TYM3025
18TYL2977	18TYM2920	18TYL3083	18TYM3026
18TYL2978	18TYM2921	18TYL3084	18TYM3027
18TYL2979	18TYM2922	18TYL3085	18TYM3028
18TYL2980	18TYM2923	18TYL3086	18TYM3029
18TYL2981	18TYM2924	18TYL3087	18TYM3030
18TYL2982	18TYM2925	18TYL3088	18TYM3031
18TYL2983	18TYM2926	18TYL3089	18TYM3032
18TYL2984	18TYM2927	18TYL3090	18TYM3033
18TYL2985	18TYM2928	18TYL3091	18TYM3034
18TYL2986	18TYM2929	18TYL3092	18TYM3035
18TYL2987	18TYM2930	18TYL3093	18TYM3036
18TYL2988	18TYM2931	18TYL3094	18TYM3037
18TYL2989	18TYM2932	18TYL3095	18TYM3038
18TYL2990	18TYM2933	18TYL3096	18TYM3039
18TYL2991	18TYM2934	18TYL3097	18TYM3040
18TYL2992	18TYM2935	18TYL3098	18TYM3041
18TYL2993	18TYM2936	18TYL3099	18TYM3042
18TYL2994	18TYM2937	18TYM3000	18TYM3043

18TYM3044	18TYM3106	18TYM3149	18TYM3211
18TYM3045	18TYM3107	18TYM3150	18TYM3212
18TYM3046	18TYM3108	18TYM3151	18TYM3213
18TYM3047	18TYM3109	18TYM3152	18TYM3214
18TYM3048	18TYM3110	18TYM3153	18TYM3215
18TYM3049	18TYM3111	18TYM3154	18TYM3216
18TYM3050	18TYM3112	18TYM3155	18TYM3217
18TYM3051	18TYM3113	18TYM3156	18TYM3218
18TYM3052	18TYM3114	18TYM3157	18TYM3219
18TYM3053	18TYM3115	18TYL3277	18TYM3220
18TYM3054	18TYM3116	18TYL3278	18TYM3221
18TYM3055	18TYM3117	18TYL3279	18TYM3222
18TYM3056	18TYM3118	18TYL3280	18TYM3223
18TYL3176	18TYM3119	18TYL3281	18TYM3224
18TYL3177	18TYM3120	18TYL3282	18TYM3225
18TYL3178	18TYM3121	18TYL3283	18TYM3226
18TYL3179	18TYM3122	18TYL3284	18TYM3227
18TYL3180	18TYM3123	18TYL3285	18TYM3228
18TYL3181	18TYM3124	18TYL3286	18TYM3229
18TYL3182	18TYM3125	18TYL3287	18TYM3230
18TYL3183	18TYM3126	18TYL3288	18TYM3231
18TYL3184	18TYM3127	18TYL3289	18TYM3232
18TYL3185	18TYM3128	18TYL3290	18TYM3233
18TYL3186	18TYM3129	18TYL3291	18TYM3234
18TYL3187	18TYM3130	18TYL3292	18TYM3235
18TYL3188	18TYM3131	18TYL3293	18TYM3236
18TYL3189	18TYM3132	18TYL3294	18TYM3237
18TYL3190	18TYM3133	18TYL3295	18TYM3238
18TYL3191	18TYM3134	18TYL3296	18TYM3239
18TYL3192	18TYM3135	18TYL3297	18TYM3240
18TYL3193	18TYM3136	18TYL3298	18TYM3241
18TYL3194	18TYM3137	18TYL3299	18TYM3242
18TYL3195	18TYM3138	18TYM3200	18TYM3243
18TYL3196	18TYM3139	18TYM3201	18TYM3244
18TYL3197	18TYM3140	18TYM3202	18TYM3245
18TYL3198	18TYM3141	18TYM3203	18TYM3246
18TYL3199	18TYM3142	18TYM3204	18TYM3247
18TYM3100	18TYM3143	18TYM3205	18TYM3248
18TYM3101	18TYM3144	18TYM3206	18TYM3249
18TYM3102	18TYM3145	18TYM3207	18TYM3250
18TYM3103	18TYM3146	18TYM3208	18TYM3251
18TYM3104	18TYM3147	18TYM3209	18TYM3252
18TYM3105	18TYM3148	18TYM3210	18TYM3253

18TYM3254	18TYM3317	18TYL3480	18TYM3423
18TYM3255	18TYM3318	18TYL3481	18TYM3424
18TYM3256	18TYM3319	18TYL3482	18TYM3425
18TYM3257	18TYM3320	18TYL3483	18TYM3426
18TYL3378	18TYM3321	18TYL3484	18TYM3427
18TYL3379	18TYM3322	18TYL3485	18TYM3428
18TYL3380	18TYM3323	18TYL3486	18TYM3429
18TYL3381	18TYM3324	18TYL3487	18TYM3430
18TYL3382	18TYM3325	18TYL3488	18TYM3431
18TYL3383	18TYM3326	18TYL3489	18TYM3432
18TYL3384	18TYM3327	18TYL3490	18TYM3433
18TYL3385	18TYM3328	18TYL3491	18TYM3434
18TYL3386	18TYM3329	18TYL3492	18TYM3435
18TYL3387	18TYM3330	18TYL3493	18TYM3436
18TYL3388	18TYM3331	18TYL3494	18TYM3437
18TYL3389	18TYM3332	18TYL3495	18TYM3438
18TYL3390	18TYM3333	18TYL3496	18TYM3439
18TYL3391	18TYM3334	18TYL3497	18TYM3440
18TYL3392	18TYM3335	18TYL3498	18TYM3441
18TYL3393	18TYM3336	18TYL3499	18TYM3442
18TYL3394	18TYM3337	18TYM3400	18TYM3443
18TYL3395	18TYM3338	18TYM3401	18TYM3444
18TYL3396	18TYM3339	18TYM3402	18TYM3445
18TYL3397	18TYM3340	18TYM3403	18TYM3446
18TYL3398	18TYM3341	18TYM3404	18TYM3447
18TYL3399	18TYM3342	18TYM3405	18TYM3448
18TYM3300	18TYM3343	18TYM3406	18TYM3449
18TYM3301	18TYM3344	18TYM3407	18TYM3450
18TYM3302	18TYM3345	18TYM3408	18TYM3451
18TYM3303	18TYM3346	18TYM3409	18TYM3452
18TYM3304	18TYM3347	18TYM3410	18TYM3453
18TYM3305	18TYM3348	18TYM3411	18TYM3454
18TYM3306	18TYM3349	18TYM3412	18TYM3455
18TYM3307	18TYM3350	18TYM3413	18TYM3456
18TYM3308	18TYM3351	18TYM3414	18TYM3457
18TYM3309	18TYM3352	18TYM3415	18TYL3582
18TYM3310	18TYM3353	18TYM3416	18TYL3583
18TYM3311	18TYM3354	18TYM3417	18TYL3584
18TYM3312	18TYM3355	18TYM3418	18TYL3585
18TYM3313	18TYM3356	18TYM3419	18TYL3586
18TYM3314	18TYM3357	18TYM3420	18TYL3587
18TYM3315	18TYL3478	18TYM3421	18TYL3588
18TYM3316	18TYL3479	18TYM3422	18TYL3589

18TYL3590	18TYM3533	18TYL3696	18TYM3639
18TYL3591	18TYM3534	18TYL3697	18TYM3640
18TYL3592	18TYM3535	18TYL3698	18TYM3641
18TYL3593	18TYM3536	18TYL3699	18TYM3642
18TYL3594	18TYM3537	18TYM3600	18TYM3643
18TYL3595	18TYM3538	18TYM3601	18TYM3644
18TYL3596	18TYM3539	18TYM3602	18TYM3645
18TYL3597	18TYM3540	18TYM3603	18TYM3646
18TYL3598	18TYM3541	18TYM3604	18TYM3647
18TYL3599	18TYM3542	18TYM3605	18TYM3648
18TYM3500	18TYM3543	18TYM3606	18TYM3649
18TYM3501	18TYM3544	18TYM3607	18TYM3650
18TYM3502	18TYM3545	18TYM3608	18TYM3651
18TYM3503	18TYM3546	18TYM3609	18TYM3652
18TYM3504	18TYM3547	18TYM3610	18TYM3653
18TYM3505	18TYM3548	18TYM3611	18TYM3654
18TYM3506	18TYM3549	18TYM3612	18TYM3655
18TYM3507	18TYM3550	18TYM3613	18TYM3656
18TYM3508	18TYM3551	18TYM3614	18TYM3657
18TYM3509	18TYM3552	18TYM3615	18TYL3778
18TYM3510	18TYM3553	18TYM3616	18TYL3779
18TYM3511	18TYM3554	18TYM3617	18TYL3780
18TYM3512	18TYM3555	18TYM3618	18TYL3781
18TYM3513	18TYM3556	18TYM3619	18TYL3782
18TYM3514	18TYM3557	18TYM3620	18TYL3783
18TYM3515	18TYL3678	18TYM3621	18TYL3784
18TYM3516	18TYL3679	18TYM3622	18TYL3785
18TYM3517	18TYL3680	18TYM3623	18TYL3786
18TYM3518	18TYL3681	18TYM3624	18TYL3787
18TYM3519	18TYL3682	18TYM3625	18TYL3788
18TYM3520	18TYL3683	18TYM3626	18TYL3789
18TYM3521	18TYL3684	18TYM3627	18TYL3790
18TYM3522	18TYL3685	18TYM3628	18TYL3791
18TYM3523	18TYL3686	18TYM3629	18TYL3792
18TYM3524	18TYL3687	18TYM3630	18TYL3793
18TYM3525	18TYL3688	18TYM3631	18TYL3794
18TYM3526	18TYL3689	18TYM3632	18TYL3795
18TYM3527	18TYL3690	18TYM3633	18TYL3796
18TYM3528	18TYL3691	18TYM3634	18TYL3797
18TYM3529	18TYL3692	18TYM3635	18TYL3798
18TYM3530	18TYL3693	18TYM3636	18TYL3799
18TYM3531	18TYL3694	18TYM3637	18TYM3700
18TYM3532	18TYL3695	18TYM3638	18TYM3701

18TYM3702	18TYM3745	18TYM3808	18TYM3851
18TYM3703	18TYM3746	18TYM3809	18TYM3852
18TYM3704	18TYM3747	18TYM3810	18TYM3853
18TYM3705	18TYM3748	18TYM3811	18TYM3854
18TYM3706	18TYM3749	18TYM3812	18TYM3855
18TYM3707	18TYM3750	18TYM3813	18TYM3856
18TYM3708	18TYM3751	18TYM3814	18TYM3857
18TYM3709	18TYM3752	18TYM3815	18TYL3976
18TYM3710	18TYM3753	18TYM3816	18TYL3977
18TYM3711	18TYM3754	18TYM3817	18TYL3978
18TYM3712	18TYM3755	18TYM3818	18TYL3979
18TYM3713	18TYM3756	18TYM3819	18TYL3980
18TYM3714	18TYM3757	18TYM3820	18TYL3981
18TYM3715	18TYL3878	18TYM3821	18TYL3982
18TYM3716	18TYL3879	18TYM3822	18TYL3983
18TYM3717	18TYL3880	18TYM3823	18TYL3984
18TYM3718	18TYL3881	18TYM3824	18TYL3985
18TYM3719	18TYL3882	18TYM3825	18TYL3986
18TYM3720	18TYL3883	18TYM3826	18TYL3987
18TYM3721	18TYL3884	18TYM3827	18TYL3988
18TYM3722	18TYL3885	18TYM3828	18TYL3989
18TYM3723	18TYL3886	18TYM3829	18TYL3990
18TYM3724	18TYL3887	18TYM3830	18TYL3991
18TYM3725	18TYL3888	18TYM3831	18TYL3992
18TYM3726	18TYL3889	18TYM3832	18TYL3993
18TYM3727	18TYL3890	18TYM3833	18TYL3994
18TYM3728	18TYL3891	18TYM3834	18TYL3995
18TYM3729	18TYL3892	18TYM3835	18TYL3996
18TYM3730	18TYL3893	18TYM3836	18TYL3997
18TYM3731	18TYL3894	18TYM3837	18TYL3998
18TYM3732	18TYL3895	18TYM3838	18TYL3999
18TYM3733	18TYL3896	18TYM3839	18TYL3900
18TYM3734	18TYL3897	18TYM3840	18TYM3901
18TYM3735	18TYL3898	18TYM3841	18TYM3902
18TYM3736	18TYL3899	18TYM3842	18TYM3903
18TYM3737	18TYL3800	18TYM3843	18TYM3904
18TYM3738	18TYM3801	18TYM3844	18TYM3905
18TYM3739	18TYM3802	18TYM3845	18TYM3906
18TYM3740	18TYM3803	18TYM3846	18TYM3907
18TYM3741	18TYM3804	18TYM3847	18TYM3908
18TYM3742	18TYM3805	18TYM3848	18TYM3909
18TYM3743	18TYM3806	18TYM3849	18TYM3910
18TYM3744	18TYM3807	18TYM3850	18TYM3911

18TYM3912	18TYM3955	18TYM4016	18TYL4178
18TYM3913	18TYM3956	18TYM4017	18TYL4179
18TYM3914	18TYM3957	18TYM4018	18TYL4180
18TYM3915	18TYL4076	18TYM4019	18TYL4181
18TYM3916	18TYL4077	18TYM4020	18TYL4182
18TYM3917	18TYL4078	18TYM4021	18TYL4183
18TYM3918	18TYL4079	18TYM4022	18TYL4184
18TYM3919	18TYL4080	18TYM4023	18TYL4185
18TYM3920	18TYL4081	18TYM4024	18TYL4186
18TYM3921	18TYL4082	18TYM4025	18TYL4187
18TYM3922	18TYL4083	18TYM4026	18TYL4188
18TYM3923	18TYL4084	18TYM4027	18TYL4189
18TYM3924	18TYL4085	18TYM4028	18TYL4190
18TYM3925	18TYL4086	18TYM4029	18TYL4191
18TYM3926	18TYL4087	18TYM4030	18TYL4192
18TYM3927	18TYL4088	18TYM4031	18TYL4193
18TYM3928	18TYL4089	18TYM4032	18TYL4194
18TYM3929	18TYL4090	18TYM4033	18TYL4195
18TYM3930	18TYL4091	18TYM4034	18TYL4196
18TYM3931	18TYL4092	18TYM4035	18TYL4197
18TYM3932	18TYL4093	18TYM4036	18TYL4198
18TYM3933	18TYL4094	18TYM4037	18TYL4199
18TYM3934	18TYL4095	18TYM4038	18TYL4100
18TYM3935	18TYL4096	18TYM4039	18TYM4101
18TYM3936	18TYL4097	18TYM4040	18TYM4102
18TYM3937	18TYL4098	18TYM4041	18TYM4103
18TYM3938	18TYL4099	18TYM4042	18TYM4104
18TYM3939	18TYL4000	18TYM4043	18TYM4105
18TYM3940	18TYM4001	18TYM4044	18TYM4106
18TYM3941	18TYM4002	18TYM4045	18TYM4107
18TYM3942	18TYM4003	18TYM4046	18TYM4108
18TYM3943	18TYM4004	18TYM4047	18TYM4109
18TYM3944	18TYM4005	18TYM4048	18TYM4110
18TYM3945	18TYM4006	18TYM4049	18TYM4111
18TYM3946	18TYM4007	18TYM4050	18TYM4112
18TYM3947	18TYM4008	18TYM4051	18TYM4113
18TYM3948	18TYM4009	18TYM4052	18TYM4114
18TYM3949	18TYM4010	18TYM4053	18TYM4115
18TYM3950	18TYM4011	18TYM4054	18TYM4116
18TYM3951	18TYM4012	18TYM4055	18TYM4117
18TYM3952	18TYM4013	18TYM4056	18TYM4118
18TYM3953	18TYM4014	18TYM4057	18TYM4119
18TYM3954	18TYM4015	18TYL4177	18TYM4120

18TYM4121	18TYL4284	18TYM4230	18TYM4301
18TYM4122	18TYL4285	18TYM4231	18TYM4302
18TYM4123	18TYL4288	18TYM4232	18TYM4303
18TYM4124	18TYL4289	18TYM4233	18TYM4304
18TYM4125	18TYL4291	18TYM4234	18TYM4305
18TYM4126	18TYL4292	18TYM4235	18TYM4306
18TYM4127	18TYL4293	18TYM4236	18TYM4307
18TYM4128	18TYL4294	18TYM4237	18TYM4308
18TYM4129	18TYL4295	18TYM4238	18TYM4309
18TYM4130	18TYL4296	18TYM4239	18TYM4310
18TYM4131	18TYL4297	18TYM4240	18TYM4311
18TYM4132	18TYL4298	18TYM4241	18TYM4312
18TYM4133	18TYL4299	18TYM4242	18TYM4313
18TYM4134	18TYL4200	18TYM4243	18TYM4314
18TYM4135	18TYM4201	18TYM4244	18TYM4315
18TYM4136	18TYM4202	18TYM4245	18TYM4316
18TYM4137	18TYM4203	18TYM4246	18TYM4317
18TYM4138	18TYM4204	18TYM4247	18TYM4318
18TYM4139	18TYM4205	18TYM4248	18TYM4319
18TYM4140	18TYM4206	18TYM4249	18TYM4320
18TYM4141	18TYM4207	18TYM4250	18TYM4321
18TYM4142	18TYM4208	18TYM4251	18TYM4322
18TYM4143	18TYM4209	18TYM4252	18TYM4323
18TYM4144	18TYM4210	18TYM4253	18TYM4324
18TYM4145	18TYM4211	18TYM4254	18TYM4325
18TYM4146	18TYM4212	18TYM4255	18TYM4326
18TYM4147	18TYM4213	18TYM4256	18TYM4327
18TYM4148	18TYM4214	18TYL4378	18TYM4328
18TYM4149	18TYM4215	18TYL4379	18TYM4329
18TYM4150	18TYM4216	18TYL4384	18TYM4330
18TYM4151	18TYM4217	18TYL4385	18TYM4331
18TYM4152	18TYM4218	18TYL4386	18TYM4332
18TYM4153	18TYM4219	18TYL4387	18TYM4333
18TYM4154	18TYM4220	18TYL4388	18TYM4334
18TYM4155	18TYM4221	18TYL4390	18TYM4335
18TYM4156	18TYM4222	18TYL4391	18TYM4336
18TYM4157	18TYM4223	18TYL4393	18TYM4337
18TYL4278	18TYM4224	18TYL4394	18TYM4338
18TYL4279	18TYM4225	18TYL4395	18TYM4339
18TYL4280	18TYM4226	18TYL4396	18TYM4340
18TYL4281	18TYM4227	18TYL4398	18TYM4341
18TYL4282	18TYM4228	18TYL4399	18TYM4342
18TYL4283	18TYM4229	18TYL4300	18TYM4343

18TYM4344	18TYM4409	18TYM4452	18TYM4516
18TYM4345	18TYM4410	18TYM4453	18TYM4517
18TYM4346	18TYM4411	18TYM4454	18TYM4518
18TYM4347	18TYM4412	18TYM4455	18TYM4519
18TYM4348	18TYM4413	18TYM4456	18TYM4520
18TYM4349	18TYM4414	18TYM4457	18TYM4521
18TYM4350	18TYM4415	18TYL4578	18TYM4522
18TYM4351	18TYM4416	18TYL4579	18TYM4523
18TYM4352	18TYM4417	18TYL4580	18TYM4524
18TYM4353	18TYM4418	18TYL4581	18TYM4525
18TYM4354	18TYM4419	18TYL4582	18TYM4526
18TYM4355	18TYM4420	18TYL4583	18TYM4527
18TYM4356	18TYM4421	18TYL4584	18TYM4528
18TYM4357	18TYM4422	18TYL4585	18TYM4529
18TYL4479	18TYM4423	18TYL4586	18TYM4530
18TYL4480	18TYM4424	18TYL4587	18TYM4531
18TYL4481	18TYM4425	18TYL4588	18TYM4532
18TYL4482	18TYM4426	18TYL4589	18TYM4533
18TYL4483	18TYM4427	18TYL4590	18TYM4534
18TYL4484	18TYM4428	18TYL4591	18TYM4535
18TYL4485	18TYM4429	18TYL4592	18TYM4536
18TYL4486	18TYM4430	18TYL4593	18TYM4537
18TYL4487	18TYM4431	18TYL4594	18TYM4538
18TYL4488	18TYM4432	18TYL4595	18TYM4539
18TYL4489	18TYM4433	18TYL4597	18TYM4540
18TYL4490	18TYM4434	18TYL4598	18TYM4541
18TYL4491	18TYM4435	18TYL4599	18TYM4542
18TYL4492	18TYM4436	18TYL4500	18TYM4543
18TYL4493	18TYM4437	18TYM4501	18TYM4544
18TYL4494	18TYM4438	18TYM4502	18TYM4545
18TYL4496	18TYM4439	18TYM4503	18TYM4546
18TYL4497	18TYM4440	18TYM4504	18TYM4547
18TYL4498	18TYM4441	18TYM4505	18TYM4548
18TYL4499	18TYM4442	18TYM4506	18TYM4549
18TYL4400	18TYM4443	18TYM4507	18TYM4550
18TYM4401	18TYM4444	18TYM4508	18TYM4551
18TYM4402	18TYM4445	18TYM4509	18TYM4552
18TYM4403	18TYM4446	18TYM4510	18TYM4553
18TYM4404	18TYM4447	18TYM4511	18TYM4554
18TYM4405	18TYM4448	18TYM4512	18TYM4555
18TYM4406	18TYM4449	18TYM4513	18TYM4556
18TYM4407	18TYM4450	18TYM4514	18TYM4557
18TYM4408	18TYM4451	18TYM4515	18TYL4682

18TYL4683	18TYM4626	18TYL4793	18TYM4736
18TYL4684	18TYM4627	18TYL4794	18TYM4737
18TYL4685	18TYM4628	18TYL4795	18TYM4738
18TYL4686	18TYM4629	18TYL4796	18TYM4739
18TYL4687	18TYM4630	18TYL4797	18TYM4740
18TYL4688	18TYM4631	18TYL4798	18TYM4741
18TYL4689	18TYM4632	18TYL4799	18TYM4742
18TYL4690	18TYM4633	18TYL4700	18TYM4743
18TYL4691	18TYM4634	18TYM4701	18TYM4744
18TYL4692	18TYM4635	18TYM4702	18TYM4745
18TYL4693	18TYM4636	18TYM4703	18TYM4746
18TYL4694	18TYM4637	18TYM4704	18TYM4747
18TYL4695	18TYM4638	18TYM4705	18TYM4748
18TYL4696	18TYM4639	18TYM4706	18TYM4749
18TYL4697	18TYM4640	18TYM4707	18TYM4750
18TYL4698	18TYM4641	18TYM4708	18TYM4751
18TYL4699	18TYM4642	18TYM4709	18TYM4752
18TYL4600	18TYM4643	18TYM4710	18TYM4753
18TYM4601	18TYM4644	18TYM4711	18TYM4754
18TYM4602	18TYM4645	18TYM4712	18TYM4755
18TYM4603	18TYM4646	18TYM4713	18TYM4756
18TYM4604	18TYM4647	18TYM4714	18TYM4757
18TYM4605	18TYM4648	18TYM4715	18TYL4881
18TYM4606	18TYM4649	18TYM4716	18TYL4882
18TYM4607	18TYM4650	18TYM4717	18TYL4883
18TYM4608	18TYM4651	18TYM4718	18TYL4884
18TYM4609	18TYM4652	18TYM4719	18TYL4885
18TYM4610	18TYM4653	18TYM4720	18TYL4886
18TYM4611	18TYM4654	18TYM4721	18TYL4887
18TYM4612	18TYM4655	18TYM4722	18TYL4888
18TYM4613	18TYM4656	18TYM4723	18TYL4889
18TYM4614	18TYM4657	18TYM4724	18TYL4890
18TYM4615	18TYL4782	18TYM4725	18TYL4891
18TYM4616	18TYL4783	18TYM4726	18TYL4892
18TYM4617	18TYL4784	18TYM4727	18TYL4893
18TYM4618	18TYL4785	18TYM4728	18TYL4894
18TYM4619	18TYL4786	18TYM4729	18TYL4895
18TYM4620	18TYL4787	18TYM4730	18TYL4896
18TYM4621	18TYL4788	18TYM4731	18TYL4897
18TYM4622	18TYL4789	18TYM4732	18TYL4898
18TYM4623	18TYL4790	18TYM4733	18TYL4899
18TYM4624	18TYL4791	18TYM4734	18TYL4800
18TYM4625	18TYL4792	18TYM4735	18TYM4801

18TYM4802	18TYM4845	18TYM4909	18TBG4952
18TYM4803	18TYM4846	18TYM4910	18TBG4953
18TYM4804	18TYM4847	18TYM4911	18TBG4954
18TYM4805	18TYM4848	18TYM4912	18TBG4955
18TYM4806	18TYM4849	18TYM4913	18TBG4956
18TYM4807	18TYM4850	18TYM4914	18TBG4957
18TYM4808	18TYM4851	18TYM4915	18TYL5080
18TYM4809	18TYM4852	18TYM4916	18TYL5081
18TYM4810	18TYM4853	18TYM4917	18TYL5082
18TYM4811	18TYM4854	18TYM4918	18TYL5083
18TYM4812	18TYM4855	18TYM4919	18TYL5084
18TYM4813	18TYM4856	18TYM4920	18TYL5085
18TYM4814	18TYM4857	18TYM4921	18TYL5086
18TYM4815	18TYL4979	18TYM4922	18TYL5087
18TYM4816	18TYL4980	18TYM4923	18TYL5088
18TYM4817	18TYL4981	18TYM4924	18TYL5089
18TYM4818	18TYL4982	18TYM4925	18TYL5090
18TYM4819	18TYL4983	18TYM4926	18TYL5091
18TYM4820	18TYL4984	18TYM4927	18TYL5092
18TYM4821	18TYL4985	18TYM4928	18TYL5093
18TYM4822	18TYL4986	18TYM4929	18TYL5094
18TYM4823	18TYL4987	18TYM4930	18TYL5095
18TYM4824	18TYL4988	18TYM4931	18TYL5096
18TYM4825	18TYL4989	18TYM4932	18TYL5097
18TYM4826	18TYL4990	18TYM4933	18TYL5098
18TYM4827	18TYL4991	18TYM4934	18TYL5099
18TYM4828	18TYL4992	18TYM4935	18TYL5000
18TYM4829	18TYL4993	18TYM4936	18TYM5001
18TYM4830	18TYL4994	18TYM4937	18TYM5002
18TYM4831	18TYL4995	18TBG4938	18TYM5003
18TYM4832	18TYL4996	18TBG4939	18TYM5004
18TYM4833	18TYL4997	18TBG4940	18TYM5005
18TYM4834	18TYL4998	18TBG4941	18TYM5006
18TYM4835	18TYL4999	18TBG4942	18TYM5007
18TYM4836	18TYL4900	18TBG4943	18TYM5008
18TYM4837	18TYM4901	18TBG4944	18TYM5009
18TYM4838	18TYM4902	18TBG4945	18TBG5010
18TYM4839	18TYM4903	18TBG4946	18TBG5011
18TYM4840	18TYM4904	18TBG4947	18TBG5012
18TYM4841	18TYM4905	18TBG4948	18TBG5013
18TYM4842	18TYM4906	18TBG4949	18TBG5014
18TYM4843	18TYM4907	18TBG4950	18TBG5015
18TYM4844	18TYM4908	18TBG4951	18TBG5016

18TBG5017	18TBF5182	18TBG5125	18TBF5290
18TBG5018	18TBF5183	18TBG5126	18TBF5291
18TBG5019	18TBF5184	18TBG5127	18TBF5292
18TBG5020	18TBF5185	18TBG5128	18TBF5293
18TBG5021	18TBF5186	18TBG5129	18TBF5294
18TBG5022	18TBF5187	18TBG5130	18TBF5295
18TBG5023	18TBF5188	18TBG5131	18TBF5296
18TBG5024	18TBF5189	18TBG5132	18TBF5297
18TBG5025	18TBF5190	18TBG5133	18TBF5298
18TBG5026	18TBF5191	18TBG5134	18TBF5299
18TBG5027	18TBF5192	18TBG5135	18TBF5200
18TBG5028	18TBF5193	18TBG5136	18TBG5201
18TBG5029	18TBF5194	18TBG5137	18TBG5202
18TBG5030	18TBF5195	18TBG5138	18TBG5203
18TBG5031	18TBF5196	18TBG5139	18TBG5204
18TBG5032	18TBF5197	18TBG5140	18TBG5205
18TBG5033	18TBF5198	18TBG5141	18TBG5206
18TBG5034	18TBF5199	18TBG5142	18TBG5207
18TBG5035	18TBF5100	18TBG5143	18TBG5208
18TBG5036	18TBG5101	18TBG5144	18TBG5209
18TBG5037	18TBG5102	18TBG5145	18TBG5210
18TBG5038	18TBG5103	18TBG5146	18TBG5211
18TBG5039	18TBG5104	18TBG5147	18TBG5212
18TBG5040	18TBG5105	18TBG5148	18TBG5213
18TBG5041	18TBG5106	18TBG5149	18TBG5214
18TBG5042	18TBG5107	18TBG5150	18TBG5215
18TBG5043	18TBG5108	18TBG5151	18TBG5216
18TBG5044	18TBG5109	18TBG5152	18TBG5217
18TBG5045	18TBG5110	18TBG5153	18TBG5218
18TBG5046	18TBG5111	18TBG5154	18TBG5219
18TBG5047	18TBG5112	18TBG5155	18TBG5220
18TBG5048	18TBG5113	18TBG5156	18TBG5221
18TBG5049	18TBG5114	18TBG5157	18TBG5222
18TBG5050	18TBG5115	18TBF5280	18TBG5223
18TBG5051	18TBG5116	18TBF5281	18TBG5224
18TBG5052	18TBG5117	18TBF5282	18TBG5225
18TBG5053	18TBG5118	18TBF5283	18TBG5226
18TBG5054	18TBG5119	18TBF5284	18TBG5227
18TBG5055	18TBG5120	18TBF5285	18TBG5228
18TBG5056	18TBG5121	18TBF5286	18TBG5229
18TBG5057	18TBG5122	18TBF5287	18TBG5230
18TYL5180	18TBG5123	18TBF5288	18TBG5231
18TBF5181	18TBG5124	18TBF5289	18TBG5232

18TBG5233	18TBF5300	18TBG5343	18TBG5412
18TBG5234	18TBG5301	18TBG5344	18TBG5413
18TBG5235	18TBG5302	18TBG5345	18TBG5414
18TBG5236	18TBG5303	18TBG5346	18TBG5415
18TBG5237	18TBG5304	18TBG5347	18TBG5416
18TBG5238	18TBG5305	18TBG5348	18TBG5417
18TBG5239	18TBG5306	18TBG5349	18TBG5418
18TBG5240	18TBG5307	18TBG5350	18TBG5419
18TBG5241	18TBG5308	18TBG5351	18TBG5420
18TBG5242	18TBG5309	18TBG5352	18TBG5421
18TBG5243	18TBG5310	18TBG5353	18TBG5422
18TBG5244	18TBG5311	18TBG5354	18TBG5423
18TBG5245	18TBG5312	18TBG5355	18TBG5424
18TBG5246	18TBG5313	18TBG5356	18TBG5425
18TBG5247	18TBG5314	18TBG5357	18TBG5426
18TBG5248	18TBG5315	18TBF5484	18TBG5427
18TBG5249	18TBG5316	18TBF5485	18TBG5428
18TBG5250	18TBG5317	18TBF5486	18TBG5429
18TBG5251	18TBG5318	18TBF5487	18TBG5430
18TBG5252	18TBG5319	18TBF5488	18TBG5431
18TBG5253	18TBG5320	18TBF5489	18TBG5432
18TBG5254	18TBG5321	18TBF5490	18TBG5433
18TBG5255	18TBG5322	18TBF5491	18TBG5434
18TBG5256	18TBG5323	18TBF5492	18TBG5435
18TBG5257	18TBG5324	18TBF5493	18TBG5436
18TBF5382	18TBG5325	18TBF5494	18TBG5437
18TBF5383	18TBG5326	18TBF5495	18TBG5438
18TBF5384	18TBG5327	18TBF5496	18TBG5439
18TBF5385	18TBG5328	18TBF5497	18TBG5440
18TBF5386	18TBG5329	18TBF5498	18TBG5441
18TBF5387	18TBG5330	18TBF5499	18TBG5442
18TBF5388	18TBG5331	18TBF5400	18TBG5443
18TBF5389	18TBG5332	18TBG5401	18TBG5444
18TBF5390	18TBG5333	18TBG5402	18TBG5445
18TBF5391	18TBG5334	18TBG5403	18TBG5446
18TBF5392	18TBG5335	18TBG5404	18TBG5447
18TBF5393	18TBG5336	18TBG5405	18TBG5448
18TBF5394	18TBG5337	18TBG5406	18TBG5449
18TBF5395	18TBG5338	18TBG5407	18TBG5450
18TBF5396	18TBG5339	18TBG5408	18TBG5451
18TBF5397	18TBG5340	18TBG5409	18TBG5452
18TBF5398	18TBG5341	18TBG5410	18TBG5453
18TBF5399	18TBG5342	18TBG5411	18TBG5454

18TBG5455	18TBG5523	18TBF5689	18TBG5639
18TBG5456	18TBG5524	18TBF5690	18TBG5640
18TBG5457	18TBG5525	18TBF5698	18TBG5641
18TBF5583	18TBG5526	18TBF5699	18TBG5642
18TBF5584	18TBG5527	18TBF5600	18TBG5643
18TBF5585	18TBG5528	18TBG5601	18TBG5644
18TBF5586	18TBG5529	18TBG5602	18TBG5645
18TBF5587	18TBG5530	18TBG5603	18TBG5646
18TBF5588	18TBG5531	18TBG5604	18TBG5647
18TBF5589	18TBG5532	18TBG5605	18TBG5648
18TBF5590	18TBG5533	18TBG5606	18TBG5649
18TBF5591	18TBG5534	18TBG5607	18TBG5650
18TBF5592	18TBG5535	18TBG5608	18TBG5651
18TBF5593	18TBG5536	18TBG5609	18TBG5652
18TBF5594	18TBG5537	18TBG5610	18TBG5653
18TBF5595	18TBG5538	18TBG5611	18TBG5654
18TBF5596	18TBG5539	18TBG5612	18TBG5655
18TBF5597	18TBG5540	18TBG5613	18TBG5656
18TBF5598	18TBG5541	18TBG5614	18TBG5657
18TBF5599	18TBG5542	18TBG5615	18TBF5781
18TBF5500	18TBG5543	18TBG5616	18TBF5782
18TBG5501	18TBG5544	18TBG5617	18TBF5783
18TBG5502	18TBG5545	18TBG5618	18TBF5784
18TBG5503	18TBG5546	18TBG5619	18TBF5785
18TBG5504	18TBG5547	18TBG5620	18TBF5786
18TBG5505	18TBG5548	18TBG5621	18TBF5787
18TBG5506	18TBG5549	18TBG5622	18TBF5788
18TBG5507	18TBG5550	18TBG5623	18TBF5789
18TBG5508	18TBG5551	18TBG5624	18TBF5798
18TBG5509	18TBG5552	18TBG5625	18TBF5799
18TBG5510	18TBG5553	18TBG5626	18TBF5700
18TBG5511	18TBG5554	18TBG5627	18TBG5701
18TBG5512	18TBG5555	18TBG5628	18TBG5702
18TBG5513	18TBG5556	18TBG5629	18TBG5703
18TBG5514	18TBG5557	18TBG5630	18TBG5704
18TBG5515	18TBF5681	18TBG5631	18TBG5705
18TBG5516	18TBF5682	18TBG5632	18TBG5706
18TBG5517	18TBF5683	18TBG5633	18TBG5707
18TBG5518	18TBF5684	18TBG5634	18TBG5708
18TBG5519	18TBF5685	18TBG5635	18TBG5709
18TBG5520	18TBF5686	18TBG5636	18TBG5710
18TBG5521	18TBF5687	18TBG5637	18TBG5711
18TBG5522	18TBF5688	18TBG5638	18TBG5712

18TBG5713	18TBG5756	18TBG5833	18TBG5911
18TBG5714	18TBG5757	18TBG5834	18TBG5912
18TBG5715	18TBF5882	18TBG5835	18TBG5913
18TBG5716	18TBF5883	18TBG5836	18TBG5914
18TBG5717	18TBF5884	18TBG5837	18TBG5915
18TBG5718	18TBF5885	18TBG5838	18TBG5916
18TBG5719	18TBF5886	18TBG5839	18TBG5917
18TBG5720	18TBF5887	18TBG5840	18TBG5918
18TBG5721	18TBF5888	18TBG5841	18TBG5919
18TBG5722	18TBF5899	18TBG5842	18TBG5920
18TBG5723	18TBF5800	18TBG5843	18TBG5921
18TBG5724	18TBG5801	18TBG5844	18TBG5922
18TBG5725	18TBG5802	18TBG5845	18TBG5923
18TBG5726	18TBG5803	18TBG5846	18TBG5924
18TBG5727	18TBG5804	18TBG5847	18TBG5925
18TBG5728	18TBG5805	18TBG5848	18TBG5926
18TBG5729	18TBG5806	18TBG5849	18TBG5927
18TBG5730	18TBG5807	18TBG5850	18TBG5928
18TBG5731	18TBG5808	18TBG5851	18TBG5929
18TBG5732	18TBG5809	18TBG5852	18TBG5930
18TBG5733	18TBG5810	18TBG5853	18TBG5931
18TBG5734	18TBG5811	18TBG5854	18TBG5932
18TBG5735	18TBG5812	18TBG5855	18TBG5933
18TBG5736	18TBG5813	18TBG5856	18TBG5934
18TBG5737	18TBG5814	18TBG5857	18TBG5935
18TBG5738	18TBG5815	18TBF5982	18TBG5936
18TBG5739	18TBG5816	18TBF5983	18TBG5937
18TBG5740	18TBG5817	18TBF5984	18TBG5938
18TBG5741	18TBG5818	18TBF5985	18TBG5939
18TBG5742	18TBG5819	18TBF5986	18TBG5940
18TBG5743	18TBG5820	18TBF5987	18TBG5941
18TBG5744	18TBG5821	18TBF5999	18TBG5942
18TBG5745	18TBG5822	18TBF5900	18TBG5943
18TBG5746	18TBG5823	18TBG5901	18TBG5944
18TBG5747	18TBG5824	18TBG5902	18TBG5945
18TBG5748	18TBG5825	18TBG5903	18TBG5946
18TBG5749	18TBG5826	18TBG5904	18TBG5947
18TBG5750	18TBG5827	18TBG5905	18TBG5948
18TBG5751	18TBG5828	18TBG5906	18TBG5949
18TBG5752	18TBG5829	18TBG5907	18TBG5950
18TBG5753	18TBG5830	18TBG5908	18TBG5951
18TBG5754	18TBG5831	18TBG5909	18TBG5952
18TBG5755	18TBG5832	18TBG5910	18TBG5953

18TBG5954	18TBG6035	18TBG6117	18TBG6201
18TBG5955	18TBG6036	18TBG6118	18TBG6202
18TBG5956	18TBG6037	18TBG6119	18TBG6203
18TBG5957	18TBG6038	18TBG6120	18TBG6204
18TBF6083	18TBG6039	18TBG6121	18TBG6205
18TBF6084	18TBG6040	18TBG6122	18TBG6206
18TBF6085	18TBG6041	18TBG6123	18TBG6207
18TBF6086	18TBG6042	18TBG6124	18TBG6208
18TBF6000	18TBG6043	18TBG6125	18TBG6209
18TBG6001	18TBG6044	18TBG6126	18TBG6210
18TBG6002	18TBG6045	18TBG6127	18TBG6211
18TBG6003	18TBG6046	18TBG6128	18TBG6212
18TBG6004	18TBG6047	18TBG6129	18TBG6213
18TBG6005	18TBG6048	18TBG6130	18TBG6214
18TBG6006	18TBG6049	18TBG6131	18TBG6215
18TBG6007	18TBG6050	18TBG6132	18TBG6216
18TBG6008	18TBG6051	18TBG6133	18TBG6217
18TBG6009	18TBG6052	18TBG6134	18TBG6218
18TBG6010	18TBG6053	18TBG6135	18TBG6219
18TBG6011	18TBG6054	18TBG6136	18TBG6220
18TBG6012	18TBG6055	18TBG6137	18TBG6221
18TBG6013	18TBG6056	18TBG6138	18TBG6222
18TBG6014	18TBG6057	18TBG6139	18TBG6223
18TBG6015	18TBF6183	18TBG6140	18TBG6224
18TBG6016	18TBF6184	18TBG6141	18TBG6225
18TBG6017	18TBF6185	18TBG6142	18TBG6226
18TBG6018	18TBF6100	18TBG6143	18TBG6227
18TBG6019	18TBG6101	18TBG6144	18TBG6228
18TBG6020	18TBG6102	18TBG6145	18TBG6229
18TBG6021	18TBG6103	18TBG6146	18TBG6230
18TBG6022	18TBG6104	18TBG6147	18TBG6231
18TBG6023	18TBG6105	18TBG6148	18TBG6232
18TBG6024	18TBG6106	18TBG6149	18TBG6233
18TBG6025	18TBG6107	18TBG6150	18TBG6234
18TBG6026	18TBG6108	18TBG6151	18TBG6235
18TBG6027	18TBG6109	18TBG6152	18TBG6236
18TBG6028	18TBG6110	18TBG6153	18TBG6237
18TBG6029	18TBG6111	18TBG6154	18TBG6238
18TBG6030	18TBG6112	18TBG6155	18TBG6239
18TBG6031	18TBG6113	18TBG6156	18TBG6240
18TBG6032	18TBG6114	18TBG6157	18TBG6241
18TBG6033	18TBG6115	18TBF6283	18TBG6242
18TBG6034	18TBG6116	18TBF6284	18TBG6243

18TBG6244	18TBG6332	18TBG6423	18TBG6517
18TBG6245	18TBG6333	18TBG6424	18TBG6518
18TBG6246	18TBG6334	18TBG6425	18TBG6519
18TBG6247	18TBG6335	18TBG6426	18TBG6520
18TBG6248	18TBG6336	18TBG6427	18TBG6521
18TBG6249	18TBG6337	18TBG6428	18TBG6522
18TBG6250	18TBG6338	18TBG6429	18TBG6523
18TBG6251	18TBG6339	18TBG6430	18TBG6524
18TBG6252	18TBG6340	18TBG6431	18TBG6525
18TBG6253	18TBG6341	18TBG6432	18TBG6526
18TBG6254	18TBG6342	18TBG6433	18TBG6527
18TBG6255	18TBG6343	18TBG6434	18TBG6528
18TBG6256	18TBG6344	18TBG6435	18TBG6529
18TBG6257	18TBG6345	18TBG6436	18TBG6530
18TBG6302	18TBG6346	18TBG6437	18TBG6531
18TBG6303	18TBG6347	18TBG6438	18TBG6532
18TBG6304	18TBG6348	18TBG6439	18TBG6533
18TBG6305	18TBG6349	18TBG6440	18TBG6534
18TBG6306	18TBG6350	18TBG6441	18TBG6535
18TBG6307	18TBG6351	18TBG6442	18TBG6536
18TBG6308	18TBG6352	18TBG6443	18TBG6537
18TBG6309	18TBG6353	18TBG6444	18TBG6538
18TBG6310	18TBG6354	18TBG6445	18TBG6539
18TBG6311	18TBG6355	18TBG6446	18TBG6540
18TBG6312	18TBG6356	18TBG6447	18TBG6541
18TBG6314	18TBG6357	18TBG6448	18TBG6542
18TBG6315	18TBG6404	18TBG6449	18TBG6543
18TBG6316	18TBG6405	18TBG6450	18TBG6544
18TBG6317	18TBG6406	18TBG6451	18TBG6545
18TBG6318	18TBG6407	18TBG6452	18TBG6546
18TBG6319	18TBG6408	18TBG6453	18TBG6547
18TBG6320	18TBG6409	18TBG6454	18TBG6548
18TBG6321	18TBG6410	18TBG6455	18TBG6549
18TBG6322	18TBG6411	18TBG6456	18TBG6550
18TBG6323	18TBG6414	18TBG6457	18TBG6551
18TBG6324	18TBG6415	18TBG6505	18TBG6552
18TBG6325	18TBG6416	18TBG6506	18TBG6553
18TBG6326	18TBG6417	18TBG6507	18TBG6554
18TBG6327	18TBG6418	18TBG6508	18TBG6555
18TBG6328	18TBG6419	18TBG6509	18TBG6556
18TBG6329	18TBG6420	18TBG6514	18TBG6607
18TBG6330	18TBG6421	18TBG6515	18TBG6608
18TBG6331	18TBG6422	18TBG6516	18TBG6614

18TBG6615
18TBG6616
18TBG6617
18TBG6618
18TBG6619
18TBG6620
18TBG6621
18TBG6622
18TBG6623
18TBG6624
18TBG6625
18TBG6626
18TBG6627
18TBG6628
18TBG6629
18TBG6630
18TBG6631
18TBG6632
18TBG6633
18TBG6634
18TBG6635
18TBG6636
18TBG6637
18TBG6638
18TBG6639
18TBG6714
18TBG6715
18TBG6716
18TBG6717
18TBG6718
18TBG6719
18TBG6720
18TBG6721
18TBG6722
18TBG6723
18TBG6724

2 LiDAR Acquisition Report

2.1 PROJECT DESCRIPTION

The project area for included approximately 1741 contiguous square miles for portions of Connecticut including a buffer of 200 meters. LiDAR sensor data were collected with the Leica ALS60 sn146. No imagery was requested or delivered. The data was delivered in the UTM coordinate system, meters, zone 18, horizontal datum NAD83, vertical datum NGVD88, Geoid 09. Deliverables for the project included a raw (unclassified) calibrated LiDAR point cloud, survey control, and a final control report.

2.2 MISSION PLANNING

GPS Base Stations

Flight planning constrained all GPS baselines to a maximum of 25 miles. Three GPS base stations were required as shown.




Figure 2: GPS Stations

LiDAR Flight Plan

LiDAR was flown based on the following sensor parameters and flight plan to achieve maximum efficiency and nominal pulse densities.

SENSOR PARAMETERS	
ALS 60	
Sensor Parameters	
Flight Hours	56.4
Pulse Rate	117,900
Field of View	32 degrees
Side Lap	50%
Average Density	2 ppm

Table 1: Sensor Parameters




Figure 3: Flight Layout

CONTROL LAYOUT

A total of 39 distributed control points were planned and collected with static GPS observations as shown.




Figure 4: Control Points

2.3 ACQUISITION

Airborne LiDAR

Notice to proceed was received from Dewberry on November 2, 2010. Data were acquired between November 3 through December 11, 2010 including necessary patch flight lines due to gaps or other anomalies. All data was reviewed at the Earth Eye Orlando Corporate office prior to departing the project location. Following is the flight acquisition summary:

Connecticut Progress Report			
Date	Weather Conditions	Missions Complete	Lines Flown
11/3/2010	Clear, medium strength winds	1	15
11/4/2010	Clouds with rain	0	0
11/5/2010	Cloudy	0	0
11/6/2010	scattered clouds, light wind	1	5
11/7/2010	Cloudy and rainy	0	0
11/8/2010	Cloudy and rainy	0	0
11/9/2010	Very cloudy	0	0
11/10/2010	Clear, very strong winds	1	8
11/11/2010	Clear, high winds	2	17
11/12/2010	Clear, moderate winds	2	15
11/13/2010	Clear, light winds	2	14
11/14/2010	Clear in the morning, clouds in afternoon, light winds	2	14
11/15/2010	Very cloudy	0	0
11/16/2010	Overcast at 3000 all day, plane maintenance	0	0
11/17/2010	Cloudy, plane Maintenance	0	0
11/18/2010	Cloudy at 5000	0	0
11/19/2010	Clear in the AM and Evening, cloudy afternoon	2	13
11/20/2010	Cloudy and strong winds (60kt)	0	0
11/21/2010	Clear with moderate winds	2	14
11/22/2010	Overcast at 2000ft	0	0
11/23/2010	Overcast at 5500ft	0	0
11/24/2010	Thanksgiving Break	0	0
11/25/2010	Thanksgiving Break	0	0
11/26/2010	Thanksgiving Break	0	0
11/27/2010	Thanksgiving Break	0	0
11/28/2010	Clear until afternoon, moderate winds	2	12
11/29/2010	Clear, calm winds	2	19
11/30/2010	Overcast at 1500ft	0	0
12/1/2010	Rain all day, extreme winds (60kt)	0	0
12/2/2010	Plane repairs (cylinder, prop)	0	0
12/3/2010	Ceiling at 4000ft, Plane repairs	0	0
12/4/2010	Very cloudy, Plane repairs	0	0
12/5/2010	Very cloudy, Plane repairs	0	0
12/6/2010	Very cloudy, Snow, Plane repairs	0	0
12/7/2010	Very cloudy	0	0
12/8/2010	Mostly cloudy @ 4500	0	0
12/9/2010	Late PM clear	2	28
12/10/2010	Early AM clear	2	18
12/11/2010	Clear, moderate winds	1	18

Table 2: Flight acquisition summary

Survey Control

Compliance with the accuracy standard was ensured through the collection of GPS ground control during the acquisition of aerial LiDAR and the establishment of a GPS base station operating at the airport. In addition to the base stations, CORS bases may have been used to supplement the solutions. The following criteria were adhered to during control point collection.

1. Each point was collected during periods of very low (<2) DOP.
2. No point was collected with a base line greater than 25 miles.
3. Each point was collected at a place of constant slope so as to minimize any errors introduced through LiDAR triangulation.
4. Each point was collected at moderate intensity surfaces so any intensity based anomalies could be avoided.

Note: The base station equipment used was a Trimble R7 with a zephyr geodetic model 2 antenna. The control points were collected with a Trimble R8 integrated receiver and antenna unit.

Point	X	Y	Z	Point	X	Y	Z
1	698093.01	4620835.64	8.84	21	759605.76	4605458.34	57.68
2	712590.80	4622232.26	163.83	22	746088.54	4606301.79	24.38
3	710524.55	4635055.93	119.80	23	742032.43	4614771.09	60.89
5	707898.94	4651075.36	59.29	24	696119.06	4608862.22	35.85
6	737774.65	4654321.29	215.12	25	708106.81	4606499.07	147.70
7	752428.44	4656847.55	111.19	26	705422.94	4599507.38	101.18
8	763983.27	4649796.16	123.44	27	714792.36	4599359.27	114.11
9	764234.20	4637894.84	179.23	28	722282.65	4606086.88	138.36
10	760611.62	4629755.04	110.96	29	721957.94	4595715.82	57.27
11	751618.82	4637723.72	92.70	30	715010.96	4588961.02	51.45
12	739099.68	4640006.75	209.42	31	724712.15	4584349.10	25.72
13	726349.39	4639827.59	210.04	32	730943.52	4575898.81	3.47
14	703386.22	4645858.32	15.47	33	741491.25	4576469.44	9.96
15	721719.06	4656824.04	191.39	34	751096.36	4578878.13	2.55
16	734421.94	4627325.81	81.17	36	752082.50	4598222.32	37.51
17	742843.25	4620456.27	85.13	37	744933.08	4593442.87	13.99
18	726004.54	4629441.06	83.19	38	732552.33	4598193.97	123.31
19	731355.30	4613723.70	119.69	39	744701.83	4630089.18	203.25
20	762486.95	4616742.19	192.81				
UTM coordinate system, meters, zone 18							
horizontal datum NAD83, vertical datum NGVD88, Geoid 09							

2.4 PROCESSING

The calibration process considered all errors inherent with the equipment including errors in GPS, IMU, and sensor specific parameters. Adjustments were made to achieve a flight line to flight line data match (relative calibration) and subsequently adjusted to control for absolute accuracy. Process steps to achieve this are as follows:

3. Vertical accuracy is achieved through the adjustment to ground control survey points within the finished product. Although the base station has absolute vertical accuracy, adjustments to sensor parameters introduces vertical error that must be normalized in the final (mean) adjustment. The minimum expected horizontal accuracy was tested during the boresight process to meet or exceed the National Standard for Spatial Data Accuracy (NSSDA) for a Horizontal accuracy of 1 meter RMSE or better and a Vertical Accuracy of $RMSE(z) \leq 9.25$ cm

2.5 QA/QC

Once all lifts are horizontally and vertically calibrated a final vertical accuracy check against the control is performed. The result is analyzed against the project specified accuracy to make sure it meets the requirement. The final accuracy for this project yielded a **0.0344 meter RMSEz @ 95% confidence level**. Following are list of all control points compared to the final calibrated LiDAR surface.

Point	X	Y	Z	Z TIN	Delta
1	698093.005	4620835.643	8.84	8.8523	-0.0123
2	712590.804	4622232.256	163.83	163.8549	-0.0249
3	710524.547	4635055.934	119.8	119.7854	0.0146
5	707898.944	4651075.358	59.29	59.3159	-0.0259
6	737774.654	4654321.285	215.12	215.1237	-0.0037
7	752428.436	4656847.551	111.19	111.1021	0.0879
8	763983.273	4649796.155	123.44	123.4035	0.0365
9	764234.196	4637894.84	179.23	179.1865	0.0435
10	760611.615	4629755.038	110.96	110.9119	0.0481
11	751618.822	4637723.715	92.7	92.7003	-0.0003
12	739099.676	4640006.745	209.42	209.3916	0.0284
13	726349.389	4639827.593	210.04	210.0474	-0.0074
14	703386.222	4645858.318	15.47	15.4295	0.0405
15	721719.062	4656824.044	191.39	191.3346	0.0554
16	734421.939	4627325.814	81.17	81.1282	0.0418
17	742843.251	4620456.271	85.13	85.0947	0.0353
18	726004.538	4629441.058	83.19	83.169	0.021
19	731355.301	4613723.695	119.69	119.6775	0.0125
20	762486.953	4616742.187	192.81	192.8352	-0.0252
21	759605.757	4605458.336	57.68	57.6962	-0.0162
22	746088.535	4606301.792	24.38	24.3109	0.0691
23	742032.43	4614771.088	60.89	60.8836	0.0064
24	696119.056	4608862.22	35.85	35.8347	0.0153
25	708106.805	4606499.071	147.7	147.7071	-0.0071
26	705422.943	4599507.381	101.18	101.1703	0.0097
27	714792.356	4599359.266	114.11	114.1564	-0.0464
28	722282.649	4606086.879	138.36	138.3688	-0.0088
29	721957.936	4595715.818	57.27	57.2781	-0.0081
30	715010.96	4588961.024	51.45	51.4595	-0.0095
31	724712.146	4584349.095	25.72	25.7126	0.0074
32	730943.521	4575898.813	3.47	3.5196	-0.0496
33	741491.247	4576469.438	9.96	9.9411	0.0189
34	751096.36	4578878.132	2.55	2.6215	-0.0715
36	752082.503	4598222.32	37.51	37.4741	0.0359
37	744933.082	4593442.871	13.99	14.0281	-0.0381
38	732552.334	4598193.97	123.31	123.2907	0.0193
39	744701.83	4630089.179	203.25	203.2495	0.0005
Final Accuracy					
Mean	-0.0079				
RMSE	0.0344				

Table 4: Final accuracy

2.6 *Final Deliverables*

Final project deliverables:

1. Calibrated raw (unclassified) LiDAR point clouds by flight line in las format
2. Survey Control points in excel format
3. Survey control accuracy report in excel format
4. Final Report PDF

Projections/Datums

UTM coordinate system, meters, zone 18, horizontal datum NAD83, vertical datum NGVD88, Geoid 09

3 LiDAR Processing & Qualitative Assessment

3.1 *Data Classification and Editing*

Earth Eye delivered LiDAR swaths to Dewberry that were calibrated and projected to project specifications. Dewberry processed the data using GeoCue and TerraScan software. The initial step is the setup of the GeoCue project, which is done by importing a project defined tile boundary index encompassing the entire project area. The acquired 3D laser point clouds, in LAS binary format, were imported into the GeoCue project and tiled according to the project tile grid. Once tiled, the laser points were classified using a proprietary routine in TerraScan. This routine removes any obvious outliers from the dataset following which the ground layer is extracted from the point cloud. The ground extraction process encompassed in this routine takes place by building an iterative surface model.

This surface model is generated using three main parameters: building size, iteration angle and iteration distance. The initial model is based on low points being selected by a "roaming window" with the assumption is that these are the ground points. The size of this roaming window is determined by the building size parameter. The low points are triangulated and the remaining points are evaluated and subsequently added to the model if they meet the iteration angle and distance constraints. This process is repeated until no additional points are added within iterations. A second critical parameter is the maximum terrain angle constraint, which determines the maximum terrain angle allowed within the classification model.

Once the initial ground routine has been performed on the data, Dewberry creates Delta Z (DZ) orthos to check the relative accuracy of the LiDAR data. These orthos compare the elevations of LiDAR points from overlapping flight lines on a 1 meter pixel cell size basis. If the elevations of points within each pixel are within 10 cm of each other, the pixel is colored green. If the elevations of points within each pixel are between 10 cm and 20 cm of each other, the pixel is colored yellow, and if the elevations of points within each pixel are greater than 20 cm in difference, the pixel is colored red. Pixels that do not contain points from overlapping flight lines are colored according to their intensity values. DZ orthos can be created using the full point cloud or ground only points and are used to review and verify the calibration of the data is acceptable. Some areas are expected to show sections or portions of red, including terrain variations, slope changes, and vegetated areas or buildings if the full point cloud is used. However, large or continuous sections of yellow or red pixels can indicate the data was not calibrated correctly or that there were issues during acquisition that could affect the usability of the data. The DZ orthos for Connecticut showed that the data was calibrated correctly with no issues that would affect its usability. The figure below shows an example of the DZ orthos.



Figure 5: DZ orthos created from ground only points. Some red pixels are visible along embankments and sloped terrain, as expected. Open, flat areas are green indicating the calibration and relative accuracy of the data is acceptable.

Dewberry utilizes a variety of software suites for data processing. After the initial ground classification, each tile was imported into Terrascan and a surface model was created to examine the ground classification. Dewberry analysts visually reviewed the ground surface model and corrected errors in the ground classification such as vegetation, buildings, and bridges that were present following the initial processing. Dewberry analysts employ 3D visualization techniques to view the point cloud at multiple angles and in profile to ensure that non-ground points are removed from the ground classification. After the ground classification corrections were completed, the dataset was processed through a water classification routine that utilizes breaklines compiled by Dewberry to automatically classify hydro features. The water classification routine selects ground points within the breakline polygons and re-classifies them as class 9, water.

Terrascan was also used to create model key points. An algorithm is defined that intelligently thins bare earth ground points so that points necessary to define breaks and elevation changes in the terrain are kept while unnecessary or redundant points are not included in the model key points. The model key points are then written to its own file, according to the project tile grid, with all points located in class 8. There were three files that did not contain enough model key points to create a file. The tiles that do not have corresponding model key points are:

- 18TXM9909
- 18TYM0056
- 18TYL4496

GeoCue was used to create the bare earth only LiDAR tiles, first return only LiDAR tiles, and last return only LiDAR tiles. For bare earth only LiDAR tiles, class 2 points are filtered from the full point cloud data and written to its own file, according to the project tile grid. There was one file that did not contain enough bare earth points to create a file. The tile that does not have corresponding bare earth points is:

- 18TYM0056

For first return and last return tiles, the desired echo return is filtered from the full point cloud and written to its own file, according to the project tile grid. The first return and last return files include the desired return from all classes. The points for these files are located in class 1. There was one file that did not contain enough first return or last return point to create a file. The tile that does not have corresponding first return or last return points is:

- 18TYM0056

After all processing and classification has been completed, GeoCue software is used to update the LAS version, projection information, creation day, and creation year of every LiDAR file.

3.2 *Qualitative Assessment*

Dewberry qualitative assessment utilizes a combination of statistical analysis and interpretative methodology to assess the quality of the data for a bare-earth digital elevation model (DEM). This process looks for anomalies in the data and also identifies areas where man-made structures or vegetation points may not have been classified properly to produce a bare-earth model.

Within this review of the LiDAR data, two fundamental questions were addressed:

- Did the LiDAR system perform to specifications?
- Did the vegetation removal process yield desirable results for the intended bare-earth terrain product?

Mapping standards today address the quality of data by quantitative methods. If the data are tested and found to be within the desired accuracy standard, then the data set is typically accepted. Now with the proliferation of LiDAR, new issues arise due to the vast amount of data. Unlike photogrammetrically-derived DEMs where point spacing can be eight meters or more, LiDAR nominal point spacing for this project is 1 point per 0.7 square meters. The end result is that millions of elevation points are measured to a level of accuracy previously unseen for traditional elevation mapping technologies and vegetated areas are measured that would be nearly impossible to survey by other means. The downside is that with millions of points, the dataset is statistically bound to have some errors both in the measurement process and in the artifact removal process.

As previously stated, the quantitative analysis addresses the quality of the data based on absolute accuracy. This accuracy is directly tied to the comparison of the discreet measurement of the survey checkpoints and that of the interpolated value within the three closest LiDAR points that constitute the vertices of a three-dimensional triangular face of the TIN. Therefore, the end result is that only a small sample of the LiDAR data is actually tested. However there is an increased level of confidence with LiDAR data due to the relative accuracy. This relative accuracy is based on how well one LiDAR point "fits" in comparison to the next contiguous LiDAR measurement, and is verified with DZ orthos. Once the absolute and relative accuracy has been ascertained, the next stage is to address the cleanliness of the data for a bare-earth DEM.

By using survey checkpoints to compare the data, the absolute accuracy is verified, but this also allows us to understand if the artifact removal process was performed correctly. To reiterate the quantitative approach, if the LiDAR sensor operated correctly over open terrain areas, then it most likely operated correctly over the vegetated areas. This does not mean that the entire bare-earth was measured; only that the elevations surveyed are most likely accurate (including elevations of treetops, rooftops, etc.). In the event that the LiDAR pulse filtered through the vegetation and was able to measure the true surface (as well as measurements on the surrounding vegetation) then the level of accuracy of the vegetation removal process can be tested as a by-product.

To fully address the data for overall accuracy and quality, the level of cleanliness (or removal of above-ground artifacts) is paramount. Since there are currently no effective automated testing procedures to measure cleanliness, Dewberry employs a combination of statistical and visualization processes. This includes creating pseudo image products such as LiDAR orthos produced from the intensity returns, Triangulated Irregular Network (TIN)'s, Digital Elevation Models (DEM) and 3-dimensional models. By creating multiple images and using overlay techniques, not only can potential errors be found, but Dewberry can also find where the data meets and exceeds expectations. This report will present representative examples where the LiDAR and post processing had issues as well as examples of where the LiDAR performed well.

Dewberry utilizes GeoCue software as the primary geospatial process management system. GeoCue is a three tier, multi-user architecture that uses .NET technology from Microsoft. .NET technology provides the real-time notification system that updates users with real-time project status, regardless of who makes changes to project entities. GeoCue uses database technology for sorting project metadata. Dewberry uses Microsoft SQL Server as the database of choice. Specific analysis is conducted in Terrascan and QT Modeler environments.

Following the completion of LiDAR point classification, the Dewberry qualitative assessment process flow for the Connecticut LiDAR project incorporated the following reviews:

1. *Format:* The LAS files are verified to meet project specifications. The LAS files conform to the specifications outlined below.
 - Format, Echos, Intensity
 - o LAS format 1.2, point data record format 1
 - o Point data record format 1
 - o Multiple returns (echos) per pulse
 - o Intensity values populated for each point
 - ASPRS classification scheme
 - o Class 1 – unclassified
 - o Class 2 – ground
 - o Class 7 – Noise
 - o Class 9 – Water
 - Projection
 - o Datum – North American Datum 1983
 - o Projected Coordinate System –UTM Zone 18N
 - o Units – Meters
 - o Vertical Datum – North American Vertical Datum 1988, Geoid 09

- Vertical Units - Meters
- LAS header information:
 - Class (Integer)
 - GPS Week Time (0.0001 seconds)
 - Easting (0.01 foot)
 - Northing (0.01 foot)
 - Elevation (0.01 foot)
 - Echo Number (Integer 1 to 4)
 - Echo (Integer 1 to 4)
 - Intensity (8 bit integer)
 - Flight Line (Integer)
 - Scan Angle (Integer degree)
- 2. *Data density, data voids:* The LAS files are used to produce Digital Elevation Models using the commercial software package “QT Modeler” which creates a 3-dimensional data model derived from Class 2 (ground points) in the LAS files. Grid spacing is based on the project density deliverable requirement for un-obscured areas. For the Connecticut LiDAR project it is stipulated that the minimum post spacing in un-obscured areas should be 1 point per 0.7 square meter.
 - a. The Connecticut LiDAR data has full coverage. Only acceptable voids (areas with no LiDAR returns in the LAS files) are present in the LiDAR, including voids caused by bodies of water.
- 3. *Bare earth quality:* Dewberry reviewed the cleanliness of the bare earth to ensure the ground has correct definition, meets the project requirements, there is correct classification of points, and there are less than 5% residual artifacts.
 - a. *Building Removal:* Large buildings, unique construction, and buildings built on sloped terrain or built into the ground can make a noticeable impact on the bare earth DEM once they have been removed, often in the form of large void areas with obvious triangulation or interpolation across the area and general lack of detail in the ground where the structure stood. Dewberry analysts verified that structures have been removed from the ground, that areas along slopes missing definition are due to structural or vegetation removal and not aggressive classification, and that holes or removal of ground is accurate. The figure below shows a unique structure in Connecticut that was partially built into the ground. While the DEM has noticeable “holes” and tinning across an embankment (Figure 7), the profile shows that these features are caused by the structure removal process and are correct (Figure 8).



Figure 6: Google Earth image of unique structure in tile 18TBF5394.




Figure 7: DEM of tile 18TBF5394. There are some large “holes” and loss of detail along the embankment on the western side of the tile that are noticeable in the DEM.




Figure 8: Profile of structure identified in tile 18TBF5394. Unclassified points are white, ground points are orange, and low noise points are red. The profile shows that the domed feature is partly built below ground

in some areas and the loss of detail along the western embankment is due to the structure being built over the embankment. The DEM surface is correct.

- b. *Hydraulic Structures:* There are hydraulic structures located on water ways and hydrologic features throughout the Connecticut project area (Figure 9). Some of these features can cause water features to appear to be floating in the final DEM (Figure 10). However, viewing the LiDAR data in profile (Figure 11) shows that the water is at the same elevation as the hydraulic structure and while it may appear to be floating above the surrounding terrain, it is correctly within a structure and not actually floating above the surrounding terrain.



Figure 9: Hydraulic structure located in tile 18TYM4611




Figure 10: DEM of tile 18TYM4611. A section of water body appears to floating above the surrounding terrain and connecting hydrologic feature.




Figure 11: LiDAR data of tile 18TYM4611. The top view shows a profile of the hydraulic structure where water points are blue and ground points are pink. The bottom view shows a TIN of the area and the location of the profile. The profile shows that the hydraulic structure has correctly been left as ground to show a barrier of the water. The water only appears to be floating because it is at the same elevation of the structure but is correctly constrained by the structure and therefore not floating.

- c. *Flight Line Ridges:* Dewberry reviewed DZ orthos to ensure acceptable calibration and relative accuracy of the Connecticut data. No major issues were identified. During manual review of the data, a limited number of flight line ridges were identified. These ridges, while somewhat visible in the final DEMs are within project specifications. An example is shown in the figure below.




Figure 12: DEMs for tiles 18TYM0939 and 18TYM0938. The flight line ridge is less than 20 cm. Overall, the Connecticut data meets the project specifications for 10cm RMSE relative accuracy.

3.4 Conclusion

The dataset conforms to project specifications for format and header values. The spatial projection information and classification of points is correct. Buildings, vegetation and other artifacts have been removed from the bare earth ground. Water features that appear to be floating by significant amounts above surrounding features are due to hydraulic structures that are present throughout the dataset. A limited number of flight line ridges are present in the dataset, but these ridges are within project specifications.

3 Survey Vertical Accuracy Checkpoints

PT. #	NORTHING	EASTING	ELEVS.
UTM Zone 18N			
POINT ID	NORTHING (M)	EASTING (M)	ELEVATION (M)
FO-1	4653267.58	710583.80	57.48
FO-2	4650474.77	725680.91	241.42
FO-3	4654265.76	737742.48	219.09
FO-4	4648614.22	757590.13	105.98
FO-5	4634319.37	758163.84	72.41
FO-6	4633196.45	746788.54	213.62
FO-7	4637837.41	734106.85	143.23
FO-8	4635710.63	701803.46	28.39
FO-9	4630782.93	719335.80	185.21
FO-10	4617047.51	703811.64	99.13
FO-11	4612436.40	723314.42	177.88

FO-12	4619654.81	734429.06	55.56
FO-13	4623199.97	757641.37	53.61
FO-14	4609018.60	752225.79	62.26
FO-15	4606871.54	739139.85	48.11
FO-16	4593928.54	727098.02	68.46
FO-17	4597256.49	713603.52	74.47
FO-18	4576720.59	728918.76	24.62
FO-19	4583351.05	737052.71	28.89
FO-20	4595389.34	754620.54	56.23
FO-21	4603740.54	763478.06	136.61
GWC-1	4643799.44	699425.78	25.75
GWC-2	4645076.29	717948.71	237.90
GWC-3	4651232.85	733720.40	281.81
GWC-4	4647726.90	752410.89	112.41
GWC-5	4638474.95	749181.87	162.07
GWC-6	4638362.57	741354.21	127.80
GWC-7	4644487.53	732675.86	242.14
GWC-8	4636611.07	713411.05	155.37
GWC-9	4625121.06	699031.72	23.15
GWC-10	4619471.38	710319.43	229.86
GWC-11	4622822.48	723806.83	86.79
GWC-12	4622180.95	743917.16	154.74
GWC-13	4612463.50	762270.63	134.59
GWC-14	4611212.56	733728.14	133.45
GWC-15	4606051.83	699950.60	35.52
GWC-16	4603187.43	712773.65	24.26
GWC-17	4600525.45	733223.07	135.65
GWC-18	4602428.66	748732.65	63.72
GWC-19	4589882.66	754004.63	16.68
GWC-20	4581299.95	749993.14	55.62
GWC-21	4580035.49	740703.63	5.20
GWC-22	4582724.00	722383.41	42.40
GWC-23	4596850.10	721561.70	85.73
OT-1	4643654.39	709202.09	66.10
OT-2	4649858.13	719006.02	161.61
OT-3	4654539.37	729194.99	279.17
OT-4	4654317.04	751150.36	134.73
OT-5	4642740.11	757797.01	73.66
OT-6	4642699.67	742250.19	151.77
OT-7	4640536.63	723271.84	139.58
OT-8	4626107.88	706699.10	79.51

OT-9	4632199.75	727335.45	166.31
OT-10	4628521.37	745512.49	116.22
OT-11	4622174.72	763746.71	89.45
OT-12	4620803.00	752274.15	65.22
OT-13	4624694.24	734890.55	88.11
OT-14	4605874.19	708291.26	127.47
OT-15	4605303.48	722061.27	106.68
OT-16	4616841.69	716819.60	137.10
OT-17	4589054.64	722720.38	20.12
OT-18	4580952.37	725414.21	12.74
OT-19	4591946.74	740889.28	38.16
OT-20	4583697.30	745267.38	52.00
OT-21	4585544.53	758801.49	28.91
OT-22	4597361.93	751717.01	39.30
OT-23	4607209.18	760988.21	76.87

Table 5: Connecticut LiDAR surveyed accuracy checkpoints

4.1 Survey Checkpoints not used in vertical accuracy testing.

Five (5) checkpoints were surveyed in non-ideal locations for testing LiDAR data. Some of these checkpoints were located on sloped terrain. Due to the horizontal spread of the sensor laser, survey checkpoints should be located on flat terrain to ensure LiDAR returns will be measuring a uniform surface and not a sloped surface which could introduce error into the vertical accuracy calculations. Additionally, some of these checkpoints were not used because they are located in land cover, such as impenetrable brush, or next to obstructions, such as trees or buildings, that do that do not give the LiDAR sensor an adequate chance to measure the ground surface.

Additional checkpoints are normally surveyed in case some of the checkpoints are deemed unusable. Even after removing these five checkpoints from the dataset, there were still 62 checkpoints remaining for the vertical accuracy testing, meeting project requirements of 60 total checkpoints comprised of 20 checkpoints in each land cover category. Table 6, below, identifies checkpoints not used in the vertical accuracy testing.

Point ID	Easting	Northing	Elevation
OT-6	742250.19	4642699.67	151.77
GWC-4	752410.89	4647726.90	112.41
FO-12	734429.06	4619654.81	55.56
GWC-14	733728.14	4611212.56	133.45
GWC-13	762270.63	4612463.50	134.59

Table 6: Checkpoints not used in vertical accuracy testing.

Below are examples of two checkpoints that were not used in vertical accuracy testing.



Figure 13: Survey Checkpoint GWC-13. This checkpoint is located on sloped terrain, better shown in the profile below.




Figure 14: DEM surface and profile showing that survey checkpoint GWC-13 is poorly placed, located on a slope, and therefore was not used in vertical accuracy testing.



Figure 15: Survey Checkpoint GWC-4. This checkpoint is located in impenetrable brush that does not adequately give the LiDAR sensor a chance to measure the ground surface. Due to the poor placement of this checkpoint, it was not used during vertical accuracy testing.

5 LiDAR Vertical Accuracy Statistics & Analysis

5.1 Background

Dewberry tests and reviews project data both quantitatively (for accuracy) and qualitatively (for usability).

For quantitative assessment (i.e. vertical accuracy assessment), sixty-seven (67) check points were surveyed for the project and are located within open terrain, grass, weeds, crops, and forest land cover categories. The checkpoints were surveyed for the project using RTK survey methods. A survey report was produced which details and validates how the survey was completed for this project.

Checkpoints were evenly distributed throughout the project area so as to cover as many flight lines as possible using the “dispersed method” of placement. Only sixty-two (62) check points were used to calculate the vertical accuracy as five (5) checkpoints were collected in inappropriate locations, such as on slopes or next to objects that would obscure LiDAR returns.

5.2 Vertical Accuracy Test Procedures

FVA (Fundamental Vertical Accuracy) is determined with check points located only in land cover category (1), open terrain (grass, dirt, sand, and/or rocks), where there is a very high probability that the LiDAR sensor will have detected the bare-earth ground surface and where random errors are expected to follow a normal error distribution. The FVA determines how well the calibrated LiDAR sensor performed. With a normal error distribution, the vertical accuracy at the 95% confidence level is computed as the vertical root mean square error (RMSEz) of the checkpoints x 1.9600. For the Connecticut LiDAR project, vertical accuracy must be 18.5 cm or less based on an RMSEz of 9.25 cm x 1.9600.

CVA (Consolidated Vertical Accuracy) is determined with all checkpoints in all land cover categories combined where there is a possibility that the LiDAR sensor and post-processing may yield elevation errors that do not follow a normal error distribution. CVA at the 95% confidence level equals the 95th percentile error for all checkpoints in all land cover categories combined. The Connecticut LiDAR Project CVA standard is 18.5 cm at the 95% confidence level. The CVA is accompanied by a listing of the 5% outliers that are larger than the 95th percentile used to compute the CVA; these are always the largest outliers that may depart from a normal error distribution. Here, Accuracy_z differs from CVA because Accuracy_z assumes elevation errors follow a normal error distribution where RMSE procedures are valid, whereas CVA assumes LiDAR errors may not follow a normal error distribution in vegetated categories, making the RMSE process invalid.

The relevant testing criteria are summarized in Table 7.

Quantitative Criteria	Measure of Acceptability
Consolidated Vertical Accuracy (CVA) in all land cover categories combined = 95% confidence lever	18.5 cm (based on combined 95 th percentile)
Fundamental Vertical Accuracy (FVA) in open terrain using RMSE _z *1.9600	18.5 cm (based on RMSE _z * 1.9600)

Table 7: Acceptance Criteria

5.3 Vertical Accuracy Testing Steps

The primary QA/QC vertical accuracy testing steps used by Dewberry are summarized as follows:

1. Dewberry's team surveyed QA/QC vertical checkpoints in accordance with the project's specifications. Figure 16 shows the location of the checkpoints.
2. Next, Dewberry interpolated the bare-earth LiDAR DEM to provide the z-value for each of the 62 checkpoints.
3. Dewberry then computed the associated z-value differences between the interpolated z-value from the LiDAR data and the ground truth survey checkpoints and computed CVA values.
4. The data were analyzed by Dewberry to assess the accuracy of the data. The review process examined the various accuracy parameters as defined by the scope of work. The overall descriptive statistics of each dataset were computed to assess any trends or anomalies. This report provides tables, graphs and figures to summarize and illustrate data quality.

Figure 16 shows the location of the QA/QC checkpoints within the project area.




Figure 16: Location of QA/QC Checkpoints

5.4 Vertical Accuracy Results

Table 8 summarizes the tested vertical accuracy resulting from a comparison of the surveyed checkpoints to the elevation values present within the LiDAR LAS files.

Land Cover Category	# of Points	FVA — Fundamental Vertical Accuracy (RMSE_z x 1.9600) Spec=0.185 m	CVA — Consolidated Vertical Accuracy (95th Percentile) Spec=0.185 m	SVA-Supplemental Vertical Accuracy (95th Percentile) Target=0.185 m
Consolidated	62		0.17	
Open Terrain	22	0.09		
Grass/Weeds/Crops	20			0.17
Forest	20			0.21

Table 8: FVA and CVA Vertical Accuracy at 95% Confidence Level

The RMSE_z for open terrain checkpoints tested 0.05 m, within the target criteria of 0.0925 m. Compared with the 0.185 m specification, the FVA tested 0.09 m at the 95% confidence level based on RMSE_z x 1.9600.

Compared with the 0.185 m specification, CVA for all checkpoints (all land cover categories combined) tested 0.17 m at the 95% confidence level based on the 95th percentile.

Supplemental vertical accuracy (SVA) is tested for each individual land cover category that is not open terrain. The SVA of each land cover category has a target value of 0.185 m at the 95% confidence level based on the 95th percentile. SVA uses target values as each land cover category tested does not have to meet the target specification as long as the consolidated vertical accuracy passes. Grass, weeds, and crops tested 0.17 m and forest tested 0.21 m compared to the 0.185 m target specification.

Figure 16 illustrates the magnitude of the differences between the QA/QC checkpoints and LiDAR data. This shows that the majority of LiDAR elevations were within +/- 0.10 m of the checkpoints elevations, but there were some outliers where LiDAR and checkpoint elevations differed by up to + 0.24 m.




Figure 16: Magnitude of Elevation Discrepancies

Table 9 lists the 5% outliers that are larger than the 95th percentile, or 0.17 meters.

pointNo	NAD 1983 UTM Zone 18N		NAVD88	LiDAR Z (m)	Delta Z
	Easting - X (m)	Northing - Y (m)	Survey Z (m)		
GWC-2	717948.71	4645076.29	237.90	238.10	0.20
FO-5	758163.84	4634319.37	72.41	72.61	0.21
FO-21	763478.06	4603740.54	136.61	136.85	0.24

Table 9: 5% Outliers

Table 10 provides overall descriptive statistics.

100 % of Totals	RMSE (m) Open Terrain Spec=0.0925 m	Mean (m)	Median (m)	Skew	Std Dev (m)	# of Points	Min (m)	Max (m)
Consolidated		0.07	0.04	0.19	0.08	62	-0.13	0.24
Open Terrain	0.05	0.04	-0.03	-0.55	0.04	22	-0.13	0.04
Grass/Weeds/Crops		0.10	0.09	-0.10	0.05	20	-0.01	0.20
Forest		0.09	0.09	0.10	0.08	20	-0.08	0.24

Table 10: Overall Descriptive Statistics

Figure 17 illustrates a histogram of the associated elevation discrepancies between the QA/QC checkpoints and elevations interpolated from the LiDAR triangulated irregular network (TIN). The frequency shows the number of discrepancies within each band of elevation differences. The discrepancies vary between a low of -0.15 m and a high of +0.24 m. The histogram shows that the majority of the discrepancies cluster around zero, but the dataset is skewed with slightly more errors on the positive side. The vast majority of points are within the ranges -0.05 m to +0.10 m.




Figure 17: Histogram of Elevation Discrepancies within errors in meters

5.5 Conclusion

Based on the vertical accuracy testing conducted by Dewberry, the LiDAR dataset for the Connecticut LiDAR Project satisfies the project's pre-defined vertical accuracy criteria.

6 Breakline Production & Qualitative Assessment Report


6.1 Breakline Production Methodology

Dewberry used GeoCue software to develop LiDAR stereo models of the Connecticut LiDAR Project area so the LiDAR derived data could be viewed in 3-D stereo using Socet Set softcopy photogrammetric software. Using LiDARgrammetry procedures with LiDAR intensity imagery, Dewberry stereo-compiled the two types of hard breaklines in accordance with the project's Data Dictionary.

All drainage breaklines are monotonically enforced to show downhill flow. Water bodies are reviewed in stereo and the lowest elevation is applied to the entire waterbody.

6.2 Breakline Qualitative Assessment

Dewberry completed breakline qualitative assessments according to a defined workflow. The following workflow diagram represents the steps taken by Dewberry to provide a thorough qualitative assessment of the breakline data.



6.3 Breakline Topology Rules

Automated checks are applied to hydro features to validate the 3D connectivity of the feature and the monotonicity of the hydrographic breaklines. Dewberry's major concern was that the hydrographic breaklines have a continuous flow downhill and that breaklines do not undulate. Error points are generated at each vertex not complying with the tested rules and these potential edit calls are then visually validated during the visual evaluation of the data. This step also helped validate that breakline vertices did not have excessive minimum or maximum elevations and that elevations are consistent with adjacent vertex elevations.

The next step is to compare the elevation of the breakline vertices against the elevation extracted from the ESRI Terrain built from the LiDAR ground points, keeping in mind that a discrepancy is expected because of the hydro-enforcement applied to the breaklines and because of the interpolated imagery used to acquire the breaklines. A given tolerance is used to validate if the elevations do not differ too much from the LiDAR.

Dewberry's final check for the breaklines was to perform a full qualitative analysis. Dewberry compared the breaklines against LiDAR intensity images to ensure breaklines were captured in the required locations. The quality control steps taken by Dewberry are outlined in the QA Checklist below.

6.4 Breakline QA/QC Checklist

Project Number/Description: TO 0002 Connecticut LiDAR

Overview

- ☒ All Feature Classes are present in GDB
- ☒ All features have been loaded into the geodatabase correctly. Ensure feature classes with subtypes are domained correctly.
- ☒ The breakline topology inside of the geodatabase has been validated. See Data Dictionary for specific rules
- ☒ Projection/coordinate system of GDB is accurate with project specifications

Perform Completeness check on breaklines using either intensity or ortho imagery

- ☒ Check entire dataset for missing features that were not captured, but should be to meet baseline specifications or for consistency (See Data Dictionary for specific collection rules). NHD data will be used to help evaluate completeness of collected hydrographic features. Features should be collected consistently across tile bounds within a dataset as well as be collected consistently between datasets.
- ☒ Check to make sure breaklines are compiled to correct tile grid boundary and there is full coverage without overlap
- ☒ Check to make sure breaklines are correctly edge-matched to adjoining datasets if applicable. Ensure breaklines from one dataset join breaklines from another dataset that are coded the same and all connecting vertices between the two datasets match in X,Y, and Z (elevation). There should be no breaklines abruptly ending at dataset boundaries and no discrepancies of Z-elevation in overlapping vertices between datasets.

Compare Breakline Z elevations to LiDAR elevations

- ☒ Using a terrain created from LiDAR ground points and water points and GeoFIRM tools, drape breaklines on terrain to compare Z values. Breakline elevations should be at or below the elevations of the immediately surrounding terrain. This should be performed before other breakline checks are completed.

Perform automated data checks using PLTS

The following data checks are performed utilizing ESRI's PLTS extension. These checks allow automated validation of 100% of the data. Error records can either be written to a table for future correction, or browsed for immediate correction. PLTS checks should always be performed on the full dataset.

- ☒ Perform “adjacent vertex elevation change check” on the Inland Ponds feature class (Elevation Difference Tolerance=.001 m). This check will return Waterbodies whose vertices are not all identical. This tool is found under “Z Value Checks.”
- ☒ Perform “unnecessary polygon boundaries check” on Inland Ponds, and Inland Streams feature classes. This tool is found under “Topology Checks.”
- ☒ Perform “duplicate geometry check” on (inland streams to inland streams), (inland ponds to inland ponds), (inland ponds to inland streams). Attributes do not need to be checked during this tool. This tool is found under “Duplicate Geometry Checks.”
- ☒ Perform “geometry on geometry check” on (inland ponds to inland streams). Spatial relationship is contains, attributes do not need to be checked. This tool is found under “Feature on Feature Checks.”
- ☒ Perform “polygon overlap/gap is sliver check” on (inland streams to inland streams), (inland ponds to inland ponds), and (inland ponds to inland streams). Maximum Polygon Area is not required. This tool is found under “Feature on Feature Checks.”

Perform Dewberry Proprietary Tool Checks

- ☒ Perform monotonicity check on inland streams features using “A3_checkMonotonicityStreamLines.” This tool looks at line direction as well as elevation. Features in the output shapefile attributed with a “d” are correct monotonically, but were compiled from low elevation to high elevation. These errors can be ignored. Features in the output shapefile attributed with an “m” are not correct monotonically and need elevations to be corrected. Input features for this tool need to be in a geodatabase. Z tolerance is .01 m. Polygons need to be exported as lines for the monotonicity tool.
- ☒ Perform connectivity check between (inland ponds to inland streams) using the tool “07_CheckConnectivityForHydro.” The input for this tool needs to be in a geodatabase. The output is a shapefile showing the location of overlapping vertices from the polygon features and polyline features that are at different Z-elevation. The unnecessary polygon boundary check must be run and all errors fixed prior to performing connectivity check. If there are exceptions to the polygon boundary rule then that feature class must be checked against itself, i.e. inland streams to inland streams.

Metadata

- ☒ Each XML file (1 per feature class) is error free as determined by the USGS MP tool
- ☒ Metadata content contains sufficient detail and all pertinent information regarding source materials, projections, datums, processing steps, etc. Content should be consistent across all feature classes.

Completion Comments: Complete – Approved



Dewberry[®]

**LiDARgrammetry Data Dictionary
& Stereo Compilation Rules**

For the Connecticut LiDAR Project

September 27, 2010

6.5.1 Horizontal and Vertical Datum

The horizontal datum shall be North American Datum of 1983, Units in meters. The vertical datum shall be referenced to the North American Vertical Datum of 1988 (NAVD 88), Units in meters. Geoid09 shall be used to convert ellipsoidal heights to orthometric heights.

6.5.2 Coordinate System and Projection

All data shall be projected to UTM Zone 18N, Horizontal Units in meters and Vertical Units in meters.

6.5.3 Inland Streams and Rivers

Feature Dataset: BREAKLINES

Feature Type: Polygon

Contains M Values: No

Annotation Subclass: None

XY Resolution: Accept Default Setting

XY Tolerance: 0.003

Feature Class: STREAMS_AND_RIVERS

Contains Z Values: Yes

Z Resolution: Accept Default Setting

Z Tolerance: 0.001

Description

This polygon feature class will depict linear hydrographic features with a width greater than 50 feet.

Table Definition

Field Name	Data Type	Allow Null Values	Default Value	Domain	Precision	Scale	Length	Responsibility
OBJECTID	Object ID							Assigned by Software
SHAPE	Geometry							Assigned by Software
SHAPE_LENGTH	Double	Yes			0	0		Calculated by Software
SHAPE_AREA	Double	Yes			0	0		Calculated by Software

Feature Definition

Description	Definition	Capture Rules
Streams and Rivers	Linear hydrographic features such as streams, rivers, canals, etc. with an average width greater than 50 feet in length. In the case of embankments, if the feature forms a natural dual line channel, then capture it consistent with the capture rules. Other natural or manmade embankments will	Capture features showing dual line (one on each side of the feature). Average width shall be greater than 50 feet to show as a double line. Each vertex placed should maintain vertical integrity and data is required to show "closed polygon". Generally both banks shall be collected to show consistent downhill flow. There are exceptions to this rule where a small branch or offshoot of the stream or river is present. The banks of the stream must be captured at the same elevation to ensure flatness of the water feature. If the elevation of the

	not qualify for this project.	<p>banks appears to be different see the task manager or PM for further guidance.</p> <p>Breaklines must be captured at or just below the elevations of the immediately surrounding terrain. Under no circumstances should a feature be elevated above the surrounding LiDAR points. Acceptable variance in the negative direction will be defined for each project individually.</p> <p>These instructions are only for docks or piers that follow the coastline or water's edge, not for docks or piers that extend perpendicular from the land into the water. If it can be reasonably determined where the edge of water most probably falls, beneath the dock or pier, then the edge of water will be collected at the elevation of the water where it can be directly measured. If there is a clearly-indicated headwall or bulkhead adjacent to the dock or pier and it is evident that the waterline is most probably adjacent to the headwall or bulkhead, then the water line will follow the headwall or bulkhead at the elevation of the water where it can be directly measured. If there is no clear indication of the location of the water's edge beneath the dock or pier, then the edge of water will follow the outer edge of the dock or pier as it is adjacent to the water, at the measured elevation of the water.</p> <p>Every effort should be made to avoid breaking a stream or river into segments.</p> <p>Dual line features shall break at road crossings (culverts). In areas where a bridge is present the dual line feature shall continue through the bridge.</p> <p>Islands: The double line stream shall be captured around an island if the features on either side of the island meet the criteria for capture. In this case a segmented polygon shall be used around the island in order to allow for the island feature to remain as a "hole" in the feature.</p>
--	-------------------------------	---

6.5.4 Inland Ponds and Lakes

Feature Dataset: BREAKLINES

Feature Type: Polygon

Contains M Values: No

Annotation Subclass: None

XY Resolution: Accept Default Setting

XY Tolerance: 0.003

Feature Class: PONDS_AND_LAKES

Contains Z Values: Yes

Z Resolution: Accept Default Setting

Z Tolerance: 0.001

Description

This polygon feature class will depict closed water body features that are at a constant elevation.

Table Definition

Field Name	Data Type	Allow Null Values	Default Value	Domain	Precision	Scale	Length	Responsibility
OBJECTID	Object ID							Assigned by Software
SHAPE	Geometry							Assigned by Software
SHAPE_LENGTH	Double	Yes			0	0		Calculated by Software
SHAPE_AREA	Double	Yes			0	0		Calculated by Software


Feature Definition

Description	Definition	Capture Rules
Ponds and Lakes	<p>Land/Water boundaries of constant elevation water bodies such as lakes, reservoirs, ponds, etc. Features shall be defined as closed polygons and contain an elevation value that reflects the best estimate of the water elevation at the time of data capture. Water body features will be captured for features 2 acres in size or greater.</p> <p>“Donuts” will exist where there are islands within a closed water body feature greater than ½ acre in size.</p>	<p>Water bodies shall be captured as closed polygons with the water feature to the right. <u>The compiler shall take care to ensure that the z-value remains consistent for all vertices placed on the water body.</u></p> <p>Breaklines must be captured at or just below the elevations of the immediately surrounding terrain. Under no circumstances should a feature be elevated above the surrounding LiDAR points. Acceptable variance in the negative direction will be defined for each project individually.</p> <p>An Island within a Closed Water Body Feature will also have a “donut polygon” compiled.</p> <p>These instructions are only for docks or piers that follow the coastline or water’s edge, not for docks or piers that extend perpendicular from the land into the water. If it can be reasonably determined where the edge of water most probably falls, beneath the dock or pier, then the edge of water will be collected at the elevation of the water where it can be directly measured. If there is a clearly-indicated headwall or bulkhead adjacent to the dock or pier and it is evident that the waterline is most probably adjacent to the headwall or bulkhead, then the water line will follow the headwall or bulkhead at the elevation of the water where it can be directly measured. If there is no clear indication of the location of the water’s edge beneath the dock or pier, then the edge of water will follow the outer edge of the dock or pier as it is adjacent to the water, at the measured elevation of the water.</p>

7 DEM Production & Qualitative Assessment

7.1

Dewberry Hydro-Flattening Workflow



DEM Production Methodology

Dewberry's utilizes ESRI software and Global Mapper for the DEM production and QC process. ArcGIS software is used to generate the products and the QC is performed in both ArcGIS and Global Mapper.

1. Generate LiDAR Stereo Pairs using GeoCue: Create stereo pairs with the raster pixel size being equal to the nominal point spacing. Stereo pairs will be created for Bare-Earth and Full-Point Cloud.
2. Extract Breaklines: Breaklines will be extracted according to the data dictionary outlined on the previous pages.
3. Classify Water Points: LAS point falling within hydrographic breaklines shall be classified to ASPRS class 9 using TerraScan. Breaklines must be prepared correctly prior to performing this task.

4. Classify Ignored Ground Points: Points within a specified distance of breaklines can be removed from the ground classification and re-classified to a separate class, usually class 10. Ignored ground points were not created for the Connecticut LiDAR project.
5. Terrain Processing: A Terrain will be generated using the Breaklines and LAS data that has been imported into Arc as a Multipoint File. If the final DEMs are to be clipped to a project boundary that boundary will be used during the generation of the Terrain.
6. Create DEM Zones for Processing: Create DEM Zones that are buffered by 2 tiles around the edges. Zones should be created in a logical manner to minimize the number of zones without creating zones too large for processing. Dewberry will make zones no larger than 200 square miles (taking into account that a DEM will fill in the entire extent not just where LiDAR is present). Once the first zone is created it must be verified against the tile grid to ensure that the cells line up perfectly with the tile grid edge.
7. Convert Terrain to Raster: Convert Terrain to raster using the DEM Zones created in step 6. In the environmental properties set the extents of the raster to the buffered Zone. For each subsequent zone, the first DEM will be utilized as the snap raster to ensure that zones consistently snap to one another.
8. Perform Initial QA/QC on Zones: During the initial QA process anomalies will be identified and corrective polygons will be created.
9. Correct Issues on Zones: Corrections on zones will be performed following Dewberry's in-house correction process.
10. Extract Individual Tiles: Individual Tiles will be extracted from the zones utilizing a Dewberry proprietary tool.
11. Final QA: Final QA will be performed on the dataset to ensure that tile boundaries are seamless.

7.2 DEM Qualitative Assessment

Dewberry performed a comprehensive qualitative assessment of the DEM deliverables to ensure that all tiled DEM products were delivered with the proper extents, were free of processing artifacts, and contained the proper referencing information. This process was performed in ArcGIS software with the use of a tool set Dewberry has developed to verify that the raster extents match those of the tile grid and contain the correct projection information. The DEM data was reviewed at a scale of 1:8000 to review for artifacts caused by the DEM generation process and to review the hydro-flattened features. Dewberry uses Global Mapper to perform this review. Corrections are applied in Arc Map. Dewberry creates HillShade models and overlays a partially transparent colorized elevation model in order to perform the corrections. The last step is to load the DEM data into Global Mapper to ensure that the corrections are acceptable, all files are readable, and that no artifacts exist between tiles. The figure below, illustrates the detail of the final DEMs and how the DEMs display elevation changes within hydrographic features.




Figure 18: DEM for tile 18TBG5110




Figure 19: Profiles showing elevation changes on hydrographic features. Some elevation changes will be shown as smooth or constant slopes (left profile and white arrow). The square pixels in a raster DEM sometimes have trouble showing constant or continuous slopes. In these areas, stair steps are used to enforce monotonic breakline elevations and flatten the hydrographic feature from bank to bank (right profile and black arrow).

7.3 DEM QA/QC Checklist

Project Number/Description: TO 00002 Connecticut LiDAR

Overview

- ☒ Correct number of files is delivered and all files are in ESRI GRID format
- ☒ Verify Raster Extents
- ☒ Verify Projection/Coordinate System

Review

- ☒ Manually review bare-earth DEMs with a hillshade to check for issues with hydro-flattening process or any general anomalies that may be present. Specifically, water should be flowing downhill, water features should NOT be floating above surrounding terrain and bridges

should NOT be present in bare-earth DEM. Hydrologic breaklines should be overlaid during review of DEMs.



DEM cell size is 1 meter



Perform final overview in Global Mapper to ensure seamless product.

Metadata



Project level DEM metadata XML file is error free as determined by the USGS MP tool



Metadata content contains sufficient detail and all pertinent information regarding source materials, projections, datums, processing steps, etc.

Completion Comments: **Complete - Approved**